

**2008**

**Virginia Department of Transportation  
Daily Traffic Volume Estimates  
Including Vehicle Classification Estimates**

where available

**Special Locality Report**

**119**

Town of Marion

Information in this report is included in Report

**86**

(Smyth County)

Prepared By

**Virginia Department of Transportation  
Traffic Engineering Division**

In Cooperation With

**U.S. Department of Transportation  
Federal Highway Administration**

Virginia Department of Transportation  
Traffic Engineering Division  
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

## Publication Notes

### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a “Combined Traffic Estimates for Parallel Roadways on this Route” or “Combined Traffic” identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate “NA” for not available.

---

VDOT’s traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating “NA” for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate “NA” for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

**Route:** The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

**Length:** Length of the traffic segment in miles.

**AADT:** Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

**QA: Quality of AADT:**

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

**4Tire:** Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

**Bus:** Percentage of the traffic volume made up of busses.

**2Axle Truck:** Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck:** Percentage of the traffic volume made up of single unit trucks with three or more axles.

**1Trail Truck:** Percentage of the traffic volume made up of units with a single trailer.

**2Trail Truck:** Percentage of the traffic volume made up of units with more than one trailer.

**QC: Quality of Classification Data:**

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

**K Factor:** The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

**QK:** Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

**Dir Factor:** The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

**AAWDT:** Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

**QW:** Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

**Year:** Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

# Route Shield Legend

## Route Systems

- North  
 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
-  US Route
-  Virginia State Route
-  Frontage Road (F precedes frontage route number)
-  Secondary Route

## Special Routes

- Bus  
 Bus - Business Route
-  Bypas - Bypass Route
-  Truck - Truck Route
- ALT  
 ALT - Alternate Route
-  Wve - Wve Route connector
-  P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
-  The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation  
 Traffic Engineering Division  
 2008  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 Town of Marion

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	
							2Axle	3+Axle	1Trail	2Trail							
	From:	WCL Marion: 86-730 Washington Ave															
11 S Main St	Town of Marion	0.52	9500	G	97%	1%	1%	0%	0%	0%	C	0.085	F	0.538	10000	G	
	To:	Greenway Ave															
11 S Main St	Town of Marion	0.40	8100	G	97%	1%	1%	0%	0%	0%	F	0.084	F	0.591	8800	G	
	To:	College St															
11 Main St	Town of Marion	0.41	8700	G	97%	1%	1%	0%	0%	0%	F	0.085	F	0.512	9400	G	
	To:	SR 16 S Commerce Street															
11 16 Main St	Town of Marion	0.08	12000	G	99%	0%	1%	0%	0%	0%	F	0.080	F	0.551	13000	G	
	To:	East Main St															
11 16 Main St	Town of Marion	0.17	15000	G	99%	0%	1%	0%	0%	0%	F	0.081	F	0.513	16000	G	
	To:	119-4453 Chatham Hill Rd; Lee St															
11 16 Main St	Town of Marion	0.94	17000	G	99%	0%	1%	0%	0%	0%	C	0.089	F	0.500	18000	G	
	To:	SR 16 Park Blvd															
11 N Main St	Town of Marion	0.20	16000	G	97%	0%	1%	0%	1%	0%	F	0.085	F		17000	G	
	To:	119-4459 Keller Lane															
11 N Main St	Town of Marion	0.65	11000	G	97%	0%	1%	0%	1%	0%	C	0.103	F	0.538	11000	G	
	To:	ECL Marion															
	From:	SCL Marion															
16 S Commerce St	Town of Marion	0.25	4800	G	95%	0%	1%	1%	3%	0%	C	0.088	F	0.553	5200	G	
	To:	I-81															
16 S Commerce St	Town of Marion	0.05	8200	G	95%	0%	1%	1%	3%	0%	F	0.087	F	0.633	8900	G	
	To:	SR 217 State St															
16 S Commerce St	Town of Marion	0.68	7600	G	95%	0%	1%	1%	3%	0%	F	0.088	F	0.535	8300	G	
	To:	US 11 Main St															
16 11 Main St	Town of Marion	0.08	12000	G	99%	0%	1%	0%	0%	0%	F	0.080	F	0.551	13000	G	
	To:	East Main St															
16 11 Main St	Town of Marion	0.17	15000	G	99%	0%	1%	0%	0%	0%	F	0.081	F	0.513	16000	G	
	To:	Chatham Hill Rd; Lee St															
16 11 Main St	Town of Marion	0.94	17000	G	99%	0%	1%	0%	0%	0%	C	0.089	F	0.500	18000	G	
	To:	US 11 Main St															
16 Park Blvd	Town of Marion	1.27	5800	G	99%	0%	0%	0%	0%	0%	C	0.088	F	0.546	6300	G	
	To:	NCL Marion															
	From:	WCL Marion															
North 81	Town of Marion (Maint: 86)	0.22	14000	G	76%	1%	1%	1%	20%	1%	F	NA			17000	G	
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		28000	G	78%	1%	1%	1%	18%	1%	F	NA			33000	G	
	To:	ECL Marion															
	From:	SCL Marion															
North 81	Town of Marion (Maint: 86)	0.27	14000	G	76%	1%	1%	1%	20%	1%	F	NA			17000	G	
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		28000	G	78%	1%	1%	1%	18%	1%	F	NA			33000	G	
	To:	SR 16 Commerce St															

Virginia Department of Transportation  
Traffic Engineering Division  
2008  
Annual Average Daily Traffic Volume Estimates By Section of Route  
Town of Marion

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
North 81	From: SR 16 Commerce St															
	Town of Marion (Maint: 86)	0.68	13000	G	76%	1%	1%	1%	20%	1%	F	NA		13000	G	
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		25000	G	78%	1%	1%	1%	18%	1%	F	NA		30000	G	
	To: NCL Marion															
South 81	From: WCL Marion															
	Town of Marion (Maint: 86)	0.22	14000	G	80%	1%	1%	1%	17%	1%	F	NA		16000	G	
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		28000	G	78%	1%	1%	1%	18%	1%	F	NA		33000	G	
	To: ECL Marion															
South 81	From: SCL Marion															
	Town of Marion (Maint: 86)	0.90	14000	G	80%	1%	1%	1%	17%	1%	F	NA		16000	G	
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		28000	G	78%	1%	1%	1%	18%	1%	F	NA		33000	G	
	To: SR 16 Commerce St															
South 81	From: SR 16 Commerce St															
	Town of Marion (Maint: 86)	0.37	13000	G	80%	1%	1%	1%	17%	1%	F	NA		16000	G	
	Combined Traffic Estimates for 2 Parallel Roadways on this Route:		25000	G	78%	1%	1%	1%	18%	1%	F	NA		30000	G	
	To: NCL Marion															
217 State St	From: Bagley Circle															
	Town of Marion (Maint: 86)	2.20	1100	G	99%	0%	0%	0%	0%	0%	C	0.122	F	0.853	1200	G
	To: SR 16 S Commerce Street															

Virginia Department of Transportation  
Traffic Engineering Division  
2008  
Annual Average Daily Traffic Volume Estimates By Section of Route  
Town of Marion

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>Town of Marion</b>																
(F9)	0.11	40	R								NA			NA		08/08/2007
From: SCL Marion																
To: SCL Marion																
(1) N Church St	0.22	1600	G	98%	1%	1%	0%	0%	0%	F	0.094	F	0.585	1700	G	2008
From: Lee Street																
To: Catron Street																
(2) Fowler St	0.02	1800	G	99%	0%	1%	0%	0%	0%	C	0.096	F	0.631	2000	G	2008
From: WCL Marion																
To: Chatham Hill Cir																
(3) Pendleton St	0.11	4400	G	98%	1%	1%	0%	0%	0%	C	0.095	F	0.545	4800	G	2008
From: Commerce St																
To: E Main St																
(4452) Poston St	0.03	330	G	99%	0%	1%	0%	0%	0%	F	0.11	F	0.621	360	G	2008
From: US 11 Main St																
To: W Cherry St																
(4452) W Cherry St	0.41	1100	G	99%	0%	1%	0%	0%	0%	F	0.109	F	0.502	1100	G	2008
From: Poston St																
To: 119-4453 S Church St																
(4452) E Cherry St	0.16	3700	G	99%	0%	1%	0%	0%	0%	C	0.108	F	0.607	4000	G	2008
From: SR 16 Commerce St																
To: SCL Marion																
(4453) S Church St	0.77	2700	G	99%	0%	1%	0%	0%	0%	F	0.097	F	0.561	3000	G	2008
From: US 11; E Main St																
To: Lee St																
(4453) N Church St	0.11	1600	G	98%	1%	1%	0%	0%	0%	C	0.092	F	0.527	1700	G	2008
From: N Church St																
To: US 11; N Main St																
(4453) Lee St	0.31	1700	G	99%	0%	0%	0%	0%	0%	C	0.104	F	0.728	1800	G	2008
From: US 11; N Main St																
To: US 11; N Main St																
(4453) Chatham Hill Rd	0.15	4500	G	98%	1%	1%	0%	0%	0%	F	0.086	F	0.597	4900	G	2008
From: Chilhowie St																
To: NCL Marion																
(4453) Chatham Hill Rd	1.16	3300	G	98%	1%	1%	0%	0%	0%	C	0.099	F	0.521	3500	G	2008
From: WCL Marion																
To: 119-1 N Church St																
(4454) Chilhowie St	0.60	3100	G	99%	1%	1%	0%	0%	0%	F	0.083	F	0.551	3300	G	2008
From: 119-1 N Church St																
To: Chilhowie St																
(4454) Chilhowie St	0.36	2400	G	99%	1%	1%	0%	0%	0%	C	0.090	F	0.589	2600	G	2008
From: Chatham Hill Rd																
To: US 11 Main St																
(4454) Chilhowie St	0.14	1500	G	99%	1%	1%	0%	0%	0%	F	0.116	F	0.903	1600	G	2008
From: US 11 Main St																
To: N Main St																
(4459) Keller Lane	0.70	1100	G	99%	0%	1%	0%	0%	0%	C	0.106	F	0.538	1200	G	2008
From: NCL Marion																
To: ECL Marion																
(4461) Johnston Rd	0.15	1700	G	95%	1%	1%	1%	2%	0%	C	0.135	F	0.734	1800	G	2008
From: US 11 Main St																
To: Look Ave																
1st St		470	G								0.1	F		510	G	2008
From: Lincoln Ave																
To: Prater Ln																
Callan Lane		3700	G	99%	0%	0%	0%	0%	0%	C	0.099	F	0.577	3700	G	2008
From: SR 16 Park Blvd																
To: Sprinkle Ave																
Catron St		360	G								0.133	F	0.556	390	G	2008
From: Wolfe Ave																
To:																

Virginia Department of Transportation  
 Traffic Engineering Division  
 2008  
 Annual Average Daily Traffic Volume Estimates By Section of Route  
 Town of Marion

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
<b>Town of Marion</b>																
From: Catron St		620	G													
To: Prescott Ave										0.094	F	0.547	670	G	2008	
From: Cumberland St		260	G													
To: Clinton Ave										0.106	F	0.522	280	G	2008	
From: Dalton St		450	G													
To: Hulldale Ave										0.117	F	0.667	490	G	2008	
From: Dogwood Dr		120	G													
To: Magnolia St										0.167	F	0.59	130	G	2008	
From: E Main St		1300	G													
To: Action Pl										0.129	F	0.775	1400	G	2008	
From: Hulldale Ave		120	G													
To: Red Oak St										0.166	F	0.509	130	G	2008	
From: Look Ave		540	G													
To: 1st Street										0.106	F	0.527	590	G	2008	
From: Magnolia St		180	G													
To: Dogwood Dr										0.126	F	0.579	190	G	2008	
From: Magnolia St		220	G													
To: Hemlock St										0.123	F	0.631	240	G	2008	
From: Mt View Dr		200	G													
To: Veteran St										0.109	F	0.529	220	G	2008	
From: Park St		480	G													
To: Golf View										0.125	F	0.626	520	G	2008	
From: Patton Ave		70	G													
To: Country Club Rd										0.152	F	0.536	80	G	2008	
From: Pearl St		590	G													
To: Dead End S Of Cherry										0.149	F	0.725	640	G	2008	
From: Prater St		2000	G	99%	0%	1%	0%	0%	0%	C	0.107	F	2000	G	2008	
To: Sprinkle Ave																
From: S Iron St		920	G													
To: Callan Ln										0.089	F		1000	G	2008	
From: Wassona Dr		1300	G													
To: E High St										0.106	F	0.617	1400	G	2008	
From: Wassona Dr		1300	G	99%	0%	0%	0%	0%	0%	C	0.107	F	1400	G	2008	
To: Walnut St																
From: Wolfe Ave		230	G													
To: Wasona Dr										0.132	F	0.548	250	G	2008	
To: Hemlock St																
To: Magnolia St																
To: Oakley St																
To: Dover St																