2002

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 142

Town of Blackstone

Prepared By

Virginia Department of Transportation Mobility Management Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Mobility Management Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management's Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT's Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

Peak Hour: The estimate of the traffic volume for the 30th highest traffic volume occurring in a one-year period divided by the AADT for the same one-year period.

QK: Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During 12 Months of Continuous Traffic Data
- B Factor based on 30th Highest Hour Observed During Less than 12 Months of Continuous Traffic Data
- Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of 30th Highest Hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the Peak Hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North
81 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.

(29) US Route

7 Virginia State Route

(600) Secondary Route

Special Routes

Bus Bus - Business Route
Bypas - Bypass Route
Truck - Truck Route
ALT ALT - Alternate Route
Wve - Wve Route connector

P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Mobility Management Division 2002 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Blackstone

						Town of Blacks	tone								
Route	Length	AADT	QA	4Tire	Bus	Tru 2Axle 3+Axle		2Trail	QC	Peak Hour	QK	Dir Factor	AAWDT	QW	Year
Town of Blackstone															
South Main Street	0.18	3900	F	95%	1%	SCL Blackston	3%	0%	F	0.098	F	0.64	3900	F	2002
	0.57	11000		From:	00/	SR 46	00/	-00/		0.004		0.554	44000	_	
South Main Street	0.57	11000	F	97%	0%	1% 0%	2%	0%	С	0.094	F	0.551	11000	F	2002
Cauth Main Chroat	0.04	44000	_	From:	00/	Tenth St	20/	00/		0.005		0.500	11000		2002
South Main Street	0.21	11000	F	97%	0%	1% 0%	2%	0%	F	0.095	F	0.582	11000	F	2002
Couth Main Street	0.47	0000	F	Fram: 96%	1%	West Entrance F	3%	0%		0.000		0.545	0000	F	2002
South Main Street	0.47	9800	г	90 76 To:	1 70	1% 0% Elm St	370	070	С	0.092	F	0.545	9800	Г	2002
Bus				From:		RT 460 BUS/RT	592								
40 (460) North Main St	0.59	7400	F	96%	1%	1% 0%	3%	0%	F	0.087	F	0.542	7400	F	2002
<u> </u>				To: From:		NORTH MAIN	ST								
40 Dinwiddie Street	0.53	1900	F	94%	0%	1% 1%	3%	0%	С	0.111	F	0.592	1900	F	2002
				To:		ECL Blackston	e								
				From:		New SCL Blackst									
46	0.15	2000	F	89%	1%	2% 1%	7%	0%	F	0.107	F	0.614	2000	F	2002
				To:		SR 40									
Bus Church Ct	0.05	2000	_	From:	40/	WCL Blackston		00/	_	0.400	_	0.504	2000	_	2002
Church St	0.25	3900	F	96%	1%	1% 0%	2%	0%	F	0.108	F	0.501	3900	F	2002
Bus				From:		Hardy St		-							
Church St	0.93	5200	F	96%	1%	1% 0%	2%	0%	С	0.097	F	0.529	5200	F	2002
~				To-		South Main St									
Bus North Main St	0.50	7400	_	From:	1%	Elm St	20/	0%	_	0.007	_	0.540	7400	_	2002
North Main St	0.59	7400	F	96%	170	1% 0%	3%	0%	F	0.087	F	0.542	7400	F	2002
Bus				From:		Dinwiddie St									
North Main St	0.14	6200	F	96%	1%	1% 0%	3%	0%	F	0.094	F	0.516	6300	F	2002
~				To: From:		Division St									
Bus 160 (North Main St	0.37	6300	F	96%	1%	1% 0%	3%	0%	F	0.089	F	0.520	6300	F	2002
North Main St	0.57	0300	•	30 /0	1 /0		3 /0	070		0.003	•	0.520	0300	'	2002
Bus				From:		Access Rd									
North Main St	0.56	4100	F	96%	1%	1% 0%	3%	0%	F	0.09	F	0.501	4100	F	2002
~				To-		ECL Blackston	e								
<u> </u>				From:		Nottoway Ave									
1 Amelia Ave	0.21	1200	F	98%	1%	1% 0%	0%	0%	С	0.093	F	0.513	1200	F	2002
				To: From:		Church St Fourth St									
1 Amelia Ave	0.21	530	F	99%	1%	0% 1%	0%	0%	С	0.110	F	0.518	530	F	2002
•				To:		Church St									
				From:		Church St									
2 Brown St	0.24	3700	F	98%	0%	1% 0%	1%	0%	С	0.096	F	0.526	3700	F	2002
				To: From:		Nottoway Ave									
2 Brown St	0.04	2900	F	98%	0%	1% 0%	1%	0%	F	0.106	F	0.553	2900	F	2002
				To		Broad St									
2 Brown St	0.33	1100	F	97%	1%	1% 0%	1%	0%	С	0.109	F	0.638	1200	F	2002
				To:		Division St									
				From:		Beach Cliff Rd									
3 College Ave	0.55	270	F	97%	1%	1% 0%	0%	0%	С	0.157	F	0.527	270	F	2002
				To-		Tenth St]							
<u> </u>			_	From:		Brown St			_		_			_	
4 Division St	0.06	960	F	97%	1%	1% 0%	0%	0%	F	0.129	F	0.635	960	F	2002
				To:		North Main St									
Counth Ct	0.44	700	_	From:	40/	South Freeman		00/	_	0.444	_	0.045	700	_	0000
5 Fourth St	0.11	790	F	97%	1%	1% 0%	0%	0%	F	0.111	F	0.615	790	F	2002
				To-		Amelia Ave									

5/13/2003 1

Virginia Department of Transportation Mobility Management Division 2002 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Blackstone

Route	Length	AADT	QA	4Tire	Bus	2Axle 3+Axle	ruck e 1Trail		- QC	Peak Hour	QK	Dir Factor	AAWDT	QW	Year
own of Blackstone				From:	ī	B-67-142 SCL Bla	ckstone	1							
6 S Freeman St	0.19	NA			J.	B-07-142 SCL Bid	ekstone			NA			NA		
0) 0 1 1001110111 01				To-		Fourth Stree	t								
				From:	67-0	665 JB-142 WCL I	Blackstone	1							
7 Nottoway Ave	0.93	NA								NA			NA		
				To:	142-592 Court House Road										
				From:		SCL Blackston									
8 Ridge Rd	0.40	1000	F	97%	1%	1% 0%	1%	0%	С	0.193	F	0.636	1000	F	2002
				To:		West Entrance	Rd								
				From:		B-67-142 New Cor	p Limits								
9 Tenth Street	0.34	110	F	99%	1%	0% 0%	0%	0%	F	0.197	F	0.531	110	F	2002
				To: From:	J.	B-67-142 Old Corp									
9 Tenth St	0.80	950	F	99%	1%	SCL Blackstor	0%	0%	С	0.118	F	0.556	950	F	2002
	0.00	330	•	To:	1 70	South Main S		070	O	0.110	•	0.000	330	•	2002
				From:											
10 Barco Road	0.20	2300	F	94%	1%	Cottage Rd Rt of	3%	0%	F	0.107	F	0.684	2300	F	2002
(10) Barco Road	0.20	2300	•	To:		US 460 BUS N. M		0 70	•	0.107	•	0.004	2300	'	2002
				From:											
591) West Entrance Rd	0.22	3000	F	98%	1%	South Main S 1% 0%	1%	0%	С	0.098	F	0.593	3000	F	2002
	0.22	3000	•	30 /0	1 70	170 070	1 /0	0 70	C	0.030	•	0.555	3000	'	2002
<u> </u>				From:	10/	Lester St	10/			2 122		2 = 2 /	4=00		
591) West Entrance Rd	0.15	1600	F	98% To:	1%	1% 0%	1%	0%	F	0.123	F	0.781	1700	F	2002
						ECL Blacksto									
<u> </u>			_	From:		WCL Blacksto					_			_	
(592) Nottoway Ave	0.83	1100	F	97%	2%	1% 0%	1%	0%	С	0.098	F	0.508	1100	F	2002
				To: From:		Courthouse R									
592 Nottoway Ave	0.07	1700	F	97%	2%	1% 0%	1%	0%	F	0.096	F	0.613	1700	F	2002
				To		Fort Ave									
(592) Nottoway Ave	0.05	1700	F	97%	2%	1% 0%	1%	0%	F	0.097	F	0.627	1700	F	2002
· · ·				To:											
592 Nottoway Ave	0.17	1900	F	From: 98%	1%	Morris St 0% 0%	1%	0%	С	0.098	F	0.644	1900	F	2002
	0.17	1300	•	Tn:	1 70	Brown St	1 /0	070	O	0.000	•	0.044	1500	ı	2002
				From:		142-2 Brown	St								
(592) Court House Rd	0.09	NA							NA			NA			
				To:	(C2US 460 Nottow	ay Ave								
				From:		Nottoway Av	re								
North West Ave	1.82	3200	F	93%	1%	1% 1%	4%	0%	С	0.098	F	0.601	3200	F	2002
				To:		SCL Blackston	ne								
				From:		Somewhere									
Some Rd		760	М	<u>. </u>						0.095	N		NA		2002
				To:		Anywhere									
				•		*									

5/13/2003 2