2002

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 217

Town of Exmore

Prepared By

Virginia Department of Transportation Mobility Management Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Mobility Management Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people at VDOT Mobility Management's Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT's Mobility Management Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

Peak Hour: The estimate of the traffic volume for the 30th highest traffic volume occurring in a one-year period divided by the AADT for the same one-year period.

QK: Quality of the Peak Hour estimate:

- A Factor based on 30th Highest Hour Observed During 12 Months of Continuous Traffic Data
- B Factor based on 30th Highest Hour Observed During Less than 12 Months of Continuous Traffic Data
- Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of 30th Highest Hour
- N Peak Hour Factor of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the Peak Hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North
81 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.

(29) US Route

7 Virginia State Route

(600) Secondary Route

Special Routes

Bus Bus - Business Route
Bypas - Bypass Route
Truck - Truck Route
ALT ALT - Alternate Route
Wve - Wve Route connector

P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.

The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

					I own of Exmore										
Route	Length	AADT	QA	4Tire	Bus	Tru 2Axle 3+Axle		2Trail	QC	Peak Hour	QK	Dir Factor	AAWDT	QW	Year
Town of Exmore				E		9.07.7		1							
(12)	0.15	17000	N	92%	1%	SCL Exmore 2% 0%	5%	0%	N	0.077	N	0.528	18000	N	2002
[13]	0.13	17000		J2 /0	170			——————————————————————————————————————	11	0.011	11	0.020	10000	11	2002
(12)	0.73	16000	G	From: 92%	1%	SR 183 Exmore 2% 0%	5%	0%	F	0.077	F	0.506	16000	G	2002
13				To:	.,,	NCL Exmore			-						
Bus				From:		SCL Exmore									
Bus 13	1.57	2300	N	96%	0%	2% 1%	1%	0%	Ν	0.093	Ν	0.5	2300	Ν	2002
<u> </u>				To:		NCL Exmore									
$\overline{}$			_	From:		US 13 Bus								_	
178	0.51	2900	G	97% To:	1%	1% 0%	1%	0%	F	0.092	F	0.510	2900	G	2002
				From:		SCL Belle Have	n								
102	0.51	1500	G	94%	1%	WCL Exmore 2% 1%	2%	0%	F	0.096	F	0.541	1500	G	2002
183	0.51	1000	Ü	To:	170	US 13 Bus	270	070		0.000		0.541	1500	O	2002
				From:		ECL Exmore									
603	0.36	2100	G	95%	1%	2% 0%	2%	0%	F	0.087	F	0.527	2100	G	2002
65				To:		US 13 BUS									
_				From:		Dead End									
693	0.03	110	R							NA			NA		04/25/20
				To:		SCL Belle Have	n								
\bigcirc				From:		65-1033									0.1/0.1/00
1001	0.06	80	R							NA			NA		04/24/20
				From:		65-1009									
1001	0.05	120	R							NA			NA		04/24/20
				To: From:		65-1010		-							
1001	0.05	260	R							NA			NA		04/24/20
				From:		65-1015		ŀ							
1001	0.05	330	R							NA			NA		04/24/20
				To: From:		65-1016		-							
1001	0.04	440	R							NA			NA		04/24/20
<u> </u>				From:		65-1017									
1001	0.06	860	R							NA			NA		04/24/20
				To: From:		US 13 BUS		-							
1001)	0.10	720	R	_						NA			NA		04/24/20
000				To:		65-1002									
	2.22		_	From:		65-603									0.4/0.4/00
1002	0.03	330	R							NA			NA		04/24/20
	2.22			From:		65-1003									0.4/0.4/00
1002	0.06	390	R							NA			NA		04/24/20
				From:		65-1001									
1002	0.22	170	R	To:		LIG 12 DI IG		i		NA			NA		04/24/20
						US 13 BUS									
	0.06	220	R	From:		US 13 BUS				NA			NA		04/24/20
1003	0.00	220	K	To:		65-1002				INA			INA		04/24/20
				From:		SR 183		1							
1004	0.04	200	R	<u> </u>		510 105				NA			NA		04/24/20
65				To		65-1024									
1004	0.06	200	R	From:		03-1024				NA			NA		04/24/20
1004				To		65 1020		 1							
1004	0.10	170	R	From:		65-1030		[NIA	NA			NA		04/24/20
1004	5.10			T		/# 1001				11/1			14/3		J Z -1/20
400)	0.18	180	R	From:		65-1031				NA			NA		04/24/20
1004	0.10	100	11	To:		65-1028		1		14/7			INA		J-1/2-1/20
						03-1020									

					I own of Exmore						
Route	Length	AADT	QA	4Tire	Bus 2Axle 3+Axle 1Trail 2Trai	()(;	eak our	QK Dir Factor	AAWDT	QW	Year
Town of Exmore				From:	65-1028	1					
1004	0.04	10	R	<u>L</u>	03-1020		NΑ		NA		04/24/200
65				To:	Dead End						
\bigcirc				From:	65-603						
1005	0.09	100	R	To:	(5.1007	1 1	۱A		NA		04/24/200
				From:	65-1007	<u> </u>					
1006	0.09	180	R	<u> </u>	65-603		NA		NA		04/24/200
65				To:	65-1007	1					
1006	0.10	90	R	From:	66 1007	1	NΑ		NA		04/24/200
65				To:	65-1034						
				From:	65-1011						
1007	0.08	40	R			_ !	۱A		NA		04/24/20
	0.07			From:	65-1005	}			N.1.A		0.4/0.4/0.0/
1007	0.07	30	R	To:	65-1006	, 1	NA		NA		04/24/200
				From:	65-1010	<u> </u>					
1008	0.15	180	R		05-1010		۱A		NA		04/10/200
65				To:	65-1017						
				From:	65-1014]					
1009	0.07	70	R			1	۱A		NA		04/10/200
				From:	65-1001]					
1009	0.09	100	R			1	NA		NA		04/10/200
	2.22	4=0	_	From:	SR 183	}					0.4.4.0.40.00
1009	0.06	170	R			-	NA		NA		04/10/200
1009 1009 1009 1009	0.10	450		From:	65-1030	J,	.1.0		NΙΔ		04/10/200
1009)	0.10	150	R	_		, ,	NΑ		NA		04/10/200
	0.03	30	R	From:	65-1031	J,	۱A		NA		04/10/200
1009	0.03	30	IX.	To:	Dead End	1 '	N/A		INA		04/10/20
				From:	65-1045						
1010	0.05	40	R			1	NA		NA		04/10/200
				To: From:	65-1026	}					
1010	0.07	70	R			1	۱A		NA		04/10/200
				From:	65-1008	<u> </u>					
1010	0.07	130	R			1	NA		NA		04/10/200
				From:	65-1014	<u> </u>					
1010	0.07	150	R	To:	65-1001	, , , , , , , , , , , , , , , , , , ,	۱A		NA		04/10/200
				From:							
1011 (65)	0.09	1100	R	<u> </u>	65-603		NA		NA		04/10/200
65				To	65-1007	1					
1011)	0.39	280	R	From:	65 1007	1	NΑ		NA		04/10/200
65				To:	Dead End	1					
				From:	SR 183						
1012 65	0.09	190	R	To:	Dood End	1 1	۱A		NA		04/10/200
				From:	Dead End	<u> </u>					
1014	0.05	40	R		65-1009	1	NA		NA		04/10/200
657				To:	65-1010						
1014)	0.06	120	R	From:	05-1010		۱A		NA		04/10/200
1014				To	65-1015	1					
1014	0.05	160	R	From:	00 1010	1	NΑ		NA		04/10/200
65				To:	65-1016	1					

					I own of Exmore								
Route	Length	AADT	QA	4Tire	Bus 2Axle 3+Axle 1Trail 2Tra	OC:	() K	Dir Factor	AAWDT	QW	Year		
Town of Exmore				From:	65-1016								
1014	0.04	160	R			N/	١		NA		04/10/200		
				To: From:	65-1017	1							
1015	0.08	45	R	r toin.	65-1014	_l N∕			NA		04/10/200		
65				To:	65-1001								
\bigcirc			_	From:	65-1014	J							
1016	0.08	100	R	To:	65-1001	N.∕	١		NA		04/10/200		
				From:	65-1043								
1017	0.15	320	R			N/	١		NA		04/10/200		
				From:	65-1027]							
1017	0.25	870	R	To:	(5.1001	N/	١.		NA		04/10/200		
				From:	65-1001	<u> </u>							
1018	0.11	250	R		US 13 BUS	J N∕	١		NA		04/10/200		
859				To:	65-1023]							
\bigcirc				From:	US 13 BUS						244242		
1019	0.04	220	R	To:	ECL EXMORE	N/	١		NA		04/10/200		
				From:	SCL EXMORE								
1021 65	0.15	570	R		See Ermone	N/	١		NA		04/10/200		
65				To:	SR 183								
022 65	0.06	60	R	From:	Dead End	_l NA			NA		04/10/200		
	0.00	60	K	To-	SR 183	7	`		INA		04/10/200		
				From:	65-1024	1							
1023	0.05	140	R			N	١		NA		04/10/200		
				From:	65-1018								
1023	0.09	120 R	120 R			NA	١		NA		04/10/200		
	0.10	00	90 R	From:	65-1025				NA		04/10/200		
1023	0.19	90	ĸ	т	65 1000	N/	١		INA		04/10/200		
1023	0.02	40	40	R	R	From:	65-1032	N/	NA		NA		04/10/200
65				To:	NCL EXMORE								
					From:	65-1004							
1024	0.08	150	R	R	R			NA	١.		NA		04/10/200
	0.11	160	R	From:	US 13 BUS	N/			NA		04/10/200		
1024	U.11	100	11	To:	65-1023		`		INA		J-7, 10/200		
1024	0.04	70	R	From:	03-1023	N/	\		NA		04/10/200		
65.7				To:	Dead End								
\bigcirc				From:	Dead End	_							
1025	0.06	6	R			NA	١.		NA		04/10/200		
	0.03	120	R	From:	65-1039	NA			NA		04/10/200		
1025	0.03	120	ĸ	Tai	LIC 12 DVIC	IN/	`		INA		U-7/ 1U/ZUU		
1025)	0.10	150	R	From:	US 13 BUS	N/	١		NA		04/10/200		
1025			-	To:	65-1023								
1025	0.09	40	R	From:	00 1025	N/			NA		04/10/200		
65/				To:	Dead End	1							
\bigcirc	6.44	000	_	From:	65-1010				N 14		04/40/222		
1026	0.11	220	R	To:	65-1044	N.∕	١		NA		04/10/200		
					00 1011	_1							

					I own of Exmore				
Route	Length	AADT	QA	4Tire	Bus 2Axle 3+Axle 1Trail 2Trail	OC:	()K	ΔΔΜΠΙ	QW Year
Town of Exmore				From:	65-1044				
1026	0.04	400	R			NA		NA	04/10/200
				To:	65-1017				
	0.09	820	R	From:	65-1017	NA		NA	04/10/20
1027	0.09	020	K	To:	US 13 BUS]		INA	04/10/20
				From:	65-1004				
1028	0.08	140	R			NA		NA	04/12/20
65				To:	SR 178				
\sim				From:	Dead End				
1029	0.04	100	R	To:	110 12 DUG	NA I		NA	04/12/20
				From:	US 13 BUS				
	0.09	100	R	From:	65-1009	NA NA		NA	04/12/20
1030	0.00	100		Ter	C# 1001	1		INZ	04/12/20
	0.08	60	R	From:	65-1004	NA		NA	04/12/20
1030	0.00	00	IX.	To:	SR 178	INA		INA	04/12/20
				From:	65-1009				
1031	0.07	130	R		00 1002	NA		NA	04/12/20
65				To: From:	65-1004				
1031	0.08	160	R	From:	00 1001	NA		NA	04/12/20
65				To:	SR 178				
\sim				From:	65-1023				
1032	0.09	170	R			NA		NA	04/12/20
				To: From:	US 13 BUS				
1032	0.03	20	R	To:	(5.1020	NA I		NA	04/12/20
				From:	65-1039				
	0.07	30	R	From:	WCL EXMORE	NA NA		NA	04/12/20
1033	0.07	30	• • • • • • • • • • • • • • • • • • • •	To:	(5.1001	1 17 1		10.0	0-1/12/20
1000	0.09	50	R	From:	65-1001	NA		NA	04/12/20
1033	0.00		•••	To:	SR 183]			0 17 12/20
				From:	65-1035				
1034	0.06	50	R			NA		NA	04/12/20
65)				To:	65-1006				
\bigcirc			_	From:	65-1034				
1035	0.06	60	R	To:	65-1036	NA I		NA	04/12/20
				From:		l I			
1026	0.08	70	R	110	Dead End	I NA		NA	04/12/20
1036	0.00	. •	•••	To:	65-1035]			0
				From:	SR 178				
1037	0.24	100	R			NA		NA	09/18/20
65)				Tn-	US 13				
\bigcirc			_	From:	Dead End				
1038	0.05	130	R			NA		NA	09/18/20
	2.25	•		From:	65-1039				00//0/==
1038	0.03	30	R	To	US 13 BUS	NA I		NA	09/18/20
				From:					
1020	0.13	520	R		SR 178	NA NA		NA	09/18/20
1039	0.10	V=V	• • • • • • • • • • • • • • • • • • • •	To:	65 1025	1		14/1	33/10/20
^	0.40	30	R	From:	65-1025	NA		NA	09/18/20
1039	0.16								

Route	Length	AADT	QA	4Tire	BusTruckTruck	(.)(.)	eak Our QK	Dir Factor	AAWDT	QW	Year
Town of Exmore											
	0.04	20	_	From:	SCL EXMORE	┙ ,	1.0		NIA		00/40/000
1041	0.04	30	R	To:	Dead End	N	IA		NA		09/18/200
	0.24	640	В	From:	SCL Exmore		1.4		NIA		00/10/200
1042	0.21	610	R	To:	US 13 BUS		IA		NA		09/18/200
				From:							
	0.14	1300	R	From:	WCL Exmore		1.4		NA		00/40/200
1043	0.14	1300	K				IA		INA		09/18/200
				From:	65-1017	_					
1043	0.08	750	R	. —		N	IA		NA		09/18/200
				To:	US 13 BUS						
				From:	65-1045						
1044	0.05	150	R	. —		N	IA		NA		09/18/200
				To	65-1026						
$\widehat{}$				From:	65-1010						
1045	0.10	40	R			N	IA		NA		09/18/200
				To:	65-1044	<u> </u>					
				From:	65-1011 SW						
1046	0.20	50	R			N	IA		NA		09/18/200
\nb				To:	65-1011 NW						