2011

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 105

Town of Clifton Forge

Information in this report is included in Report

03

(Alleghany County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	
7	Virginia State Rou	te
(F241)	Frontage Road (F	precedes frontage route number)
(600)	Secondary Route	

Special Routes

Bus	Bus - Business Route	
{29}	Bypas - Bypass Route	
	Truck - Truck Route	
ALT	ALT - Alternate Route	
(220)	Wye - Wye Route connector	

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division

2011 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Clifton Forge

								Tru	ıck			K		Dir		
Route	Jurisdiction	n Lengtl	n AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK	Factor	AAWDT	- QV
~~ ~~	From:	W	CL Clifton F	orge												
60 64 220	Town of Clifton Forge	e (Maint: 03) 1.55				See I-6	4 for dir	ectional t	raffic vo	olume est	imate	s for this	segm	ent.		
\Rightarrow \circ \Leftrightarrow	Combined Traffic Estimates for 2 Paralle			G	76%	1%	1%	1%	21%	0%	F	NA			12000	G
	To:	E	CL Clifton Fo	orge												
Bus Bus	From:		CL Clifton F													
60 (220) Ridgeway St	Town of Clifton	Forge 0.27	7800	F	98%	1%	0%	0%	0%	0%	F	0.089	F		8100	F
\times	To.		6th St				\neg \vdash									
Bus Bus 60 (220 Ridgeway St	Town of Clifton	Forge 0.61	8400	F	98%	1%	0%	0%	0%	0%	С	0.084	F		8800	
60 { 220 } Ridgeway St	Town of Ciliton	roige 0.01	0400	Г	90 /6	1 /0	0 76	0 /6	076	076	C	0.004			0000	,
Bus Bus	To: From:		Roxbury St													
60 Ridgeway St	Town of Clifton	Forge 0.14	4700	F	98%	1%	0%	0%	0%	0%	F	0.097	F		4800	-
	Combined Traffic Estimates for 2 Paralle	el Roadways on this Route	e: 8600	F	98%	0%	0%	0%	0%	0%	F	0.087	F		8900	
	Tac		Commercial A													
Bus Bus	From:															
60) (220) (188) (188) Ridgewa	y St Town of Clifton	•	4900	G								0.097	N		4900	(
~~~	Combined Traffic Estimates for 2 Paralle			G								NA			9200	(
Dura Dura	To:		us US 220 Ma													
Bus Bus 60 (220 Main St	Town of Clifton		US 220 Ridge <b>7900</b>	F	98%	0%	1%	0%	1%	0%	С	0.085	F		8200	
60 ( 220 ) Main St	rown or omitor	1 orgc 0.20			3070	070	170	070	170	070	O	0.005	•		0200	
Bus Bus	To: From:		B St													
60 (220) Main St	Town of Clifton	Forge 0.06	6600	F	98%	0%	1%	0%	1%	0%	F	0.085	F		6800	
	To:		Bus US 220													
<u>Bus</u>	From:	_	US 220 Bus													
60)	Town of Clifton		5700	F	99%	0%	1%	0%	0%	0%	С	0.093	F		5900	
~	To:	E	CL Clifton Fo	orge												
Bus Bus	From:		Ridgeway S													
60 (220) Roxbury St	Town of Clifton	Forge 0.05	5200	F	98%	0%	0%	0%	1%	0%	F	0.083	F		5400	
<del>\( \)</del>	To:		Kesswick S				_									
Bus Bus 60 (220 (Kesswick St	Town of Clifton	Forge 0.14	Roxbury St 4000	F	98%	0%	0%	0%	1%	0%	С	0.081	F		4100	
60 (220) Kesswick St		•		F		0%	0%		0%		_		F			
	Combined Traffic Estimates for 2 Paralle	Roadways on this Route	Main St		98%	0%	0%	0%	0%	0%	Г	0.087	Г		8900	
Bus Bus	From:		Kesswick S	t												
60 (220) (188) (188) Main St	Town of Clifton	Forge 0.07	4200	F	98%	0%	0%	0%	1%	0%	F	0.089	F		4400	
\$)(===)(==)(==)(==)(==)(==)(==)(==)(==)(	Combined Traffic Estimates for 2 Paralle	el Roadways on this Route	e: <b>9100</b>	G								NA			9200	
	To:		Ridgeway Str	eet												
ast	From:	W	CL Clifton F	orge												
64) 60 (220)	Town of Clifton Forge		6500	G	77%	1%	1%	1%	20%	0%	F	NA			6100	(
57 (50) (220)	Combined Traffic Estimates for 2 Paralle	• •		G	76%	1%	1%	1%	21%	0%	F	NA			12000	(
	55	E		_	. 0 / 0	. , 0	. , ,	1 /0	- 1 /0	0 / 0	•				000	,

8/27/2012 7

#### Virginia Department of Transportation Traffic Engineering Division

### 2011 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Clifton Forge

								Trι	ıck			K		Dir		
Route	Jurisdictio	n Length	AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK	Factor	AAWDT	QV
West	From:		L Clifton For	rge												
64) (60) (220)	Town of Clifton Forge	e (Maint: 03) 1.55	6400	F	76%	1%	1%	1%	21%	0%	F	NA			6000	F
$\circ \circ \circ$	Combined Traffic Estimates for 2 Parallel	el Roadways on this Route:	13000	G	76%	1%	1%	1%	21%	0%	F	NA			12000	G
	To:	EC	L Clifton For	ge												
Bus Bus	From:		Ridgeway St													
188) (60) (220) (188) Main St	Town of Clifton	Forge 0.07	4200	F	98%	0%	0%	0%	1%	0%	F	0.089	F		4400	F
100 (4) (220) (80)	Combined Traffic Estimates for 2 Paralle	-	9100	G								NA			9200	G
	To:		Keswick St												0200	
	From:	US 6	0 Par, Keswic	k St												
188)Main St	Town of Clifton	Forge 0.05	270	F	98%	1%	1%	0%	0%	0%	F	0.133	F		290	F
	Combined Traffic Estimates for 2 Parallel	el Roadways on this Route:	2200	F	98%	1%	1%	0%	0%	0%	F	0.093	F		2300	F
	To:		cCormick Blv	'd												
_	From:		Main St													
188 McCormick Blvd	Town of Clifton	Forge 0.07	250	F	98%	1%	1%	0%	0%	0%	F	0.113	F		270	F
	Combined Traffic Estimates for 2 Parallel	el Roadways on this Route:	1700	F	98%	1%	1%	0%	0%	0%	F	0.095	F		1700	F
	To:	CD 1	88 Par, Church	h C+												
188)McCormick Blvd	From: Town of Clifton		700	F	98%	1%	1%	0%	0%	0%	С	0.105	F		740	F
188 IVICCOITIICK BIVO	Town of Ciliton		Lafayette St		90 /0	1 /0	1 /0	0 /6	076	0 /0	C	0.103	Г		740	
	From:		Cormick Blv	rd.												
188) Lafayette St	Town of Clifton		260	F	98%	1%	1%	0%	0%	0%	F	0.101	F		270	F
188) Zarayono or	To:	1 0.90	Rose Ave	•	0070	170		070	070	070	•	0.101	•		2.0	•
	From:		Lafayette St													
188 Rose Ave	Town of Clifton		500	F	97%	1%	1%	0%	0%	0%	С	0.105	F		530	F
100)	To:	<u> </u>	Tremont St													
	From:		Rose Ave													
188)Tremont St	Town of Clifton	Forge 0.03	500	F	97%	1%	1%	0%	0%	0%	С	0.105	F		530	F
$\mathcal{O}$	To:		Sioux Ave													
	From:		Tremont St													
188 Sioux Ave	Town of Clifton		500	F	97%	1%	1%	0%	0%	0%	С	0.105	F		530	F
$\smile$	To:	105-	-3551 Sioux A	Ave												
Bus Bus	From:		Main St													
188) 60 (220) (188) Ridgeway	St Town of Clifton	Forge 0.07	4900	G								0.097	Ν		4900	G
	Combined Traffic Estimates for 2 Parallel	el Roadwavs on this Route:	9100	G								NA			9200	G
	To:		60 Commerci													
	From:	Bus US 60, B	us US 220, E	Ridgw	ay St											
188 Commercial Ave	Town of Clifton	Forge 0.05	1100	F	98%	1%	0%	0%	0%	0%	F	0.092	F		1200	F
• • • • • • • • • • • • • • • • • • • •	To:	Bus US 60 Par,	Due 116 220 D	Or Moi	n Straat											
188 Commercial Ave	From: Town of Clifton		1900	rar, Mai	98%	1%	0%	0%	0%	0%	E	0.092	F		2100	F
188 Confinercial Ave		0									F					F
	Combined Traffic Estimates for 2 Paralle			F	98%	1%	1%	0%	0%	0%	F	0.093	F		2300	ŀ
	From:		Church Street ommercial Av	re.												
188 Church St	Town of Clifton		1400	F	98%	1%	0%	0%	0%	0%	С	0.093	F		1500	
188 Charch St	Combined Traffic Estimates for 2 Paralle	· ·								0%	_					-
	Compined Traffic Estimates for 2 Paralle	ei Koadways on this Route:	1700	F	98%	1%	1%	0%	0%	11%	-	0.095	F		1700	F

8/27/2012

#### Virginia Department of Transportation Traffic Engineering Division

## 2011 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Clifton Forge

Route	Jurisdictio	n Le		AADT	QA	4Tire	Bus		T le 3+Axl			QC	K Factor	QK	Dir Factor	AAWDT	QW
~~~	From:			L Clifton Fo	rge												
{220} (64) {60}	Town of Clifton Forge		.55				See I-6	4 for c	directiona	l traffic v	olume es	timate	s for this	segm	ent.		
\longrightarrow \bigcirc \bigcirc	Combined Traffic Estimates for 2 Paralle	l Roadways on this R			G	76%	1%	1%	1%	21%	0%	F	NA			12000	G
	10:		WC.	L Clifton Fo	orge												
Bus	From:			L Clifton Fo													
(220) Verge Street	Town of Clifton	Forge C).70	2000	F	97%	1%	1%	0%	2%	0%	С	0.085	F		2100	F
Dura Dura	Tac Franc			Bus US 60				-									
Bus Bus 220 60 Main St	Town of Clifton	Forge (0.06	6600	F	98%	0%	1%	0%	1%	0%	F	0.085	F		6800	F
220 60 Main St	Town of Omtor	1 olgo C	7.00		<u> </u>	3070	070	1 /0	0 /0	170	070	•	0.000	•		0000	•
Bus Bus	To: From:			B ST													
(220) (60) Main St	Town of Clifton	Forge 0).26	7900	F	98%	0%	1%	0%	1%	0%	С	0.085	F		8200	F
Bus Bus	To- From:		F	Ridgeway St													
(220) (60) (188) (188) Main St	Town of Clifton	Forge 0	0.07	4200	F	98%	0%	0%	0%	1%	0%	F	0.089	F		4400	F
(220) (45) (100) (190)	Combined Traffic Estimates for 2 Paralle	el Roadways on this R	oute:	9100	G								NA			9200	G
	To:			Keswick St												0200	
Bus Bus	From:			Main St													
(220) (60) Kesswick St	Town of Clifton	Forge C).14	4000	F	98%	0%	0%	0%	1%	0%	С	0.081	F		4100	F
	Combined Traffic Estimates for 2 Paralle	el Roadways on this R	loute:	8600	F	98%	0%	0%	0%	0%	0%	F	0.087	F		8900	F
	To:			Roxbury St													
Bus Bus	From:			Keswick St													_
(220) (60) Roxbury St	Town of Clifton	Forge C	0.05	5200	F	98%	0%	0%	0%	1%	0%	F	0.083	F		5400	F
<u> </u>	To:			Ridgeway St													
Bus Bus (220) 60 Ridgeway St	Town of Clifton	Forge	0.61	Roxbury St 8400	F	98%	1%	0%	5 0%	0%	0%	С	0.084	F		8800	F
220 60 Ridgeway St	TOWN OF CHILDI	i dige C).U I		Г	30 /0	1 /0	070	0%	0 /0	0 /0	C	0.004	Г		0000	Г
Bus Bus	To: From:			6th St													
(220) (60) Ridgeway St	Town of Clifton	Forge C).27	7800	F	98%	1%	0%	0%	0%	0%	F	0.089	F		8100	F
	To:	-	WC	L Clifton Fo	rge												

8/27/2012

Virginia Department of Transportation Traffic Engineering Division 2011 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Clifton Forge

					Town of C	Clifton F	orge								
Length	AADT	QA	4Tire	Bus					QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
	From:	1			Des	ad End				-1					
0.05	290	R			200	.aa 2310				NA			NA		07/24/2008
	To														
0.34		R			105-3551	I Sioux A	ive			NA			NA		07/24/2008
	To:				Dea	ad End									0.72 .7200
	From:														
0.12	1800 To:	F	98%	1%				0%	F	0.096	F		1900	F	2011
	From:				Jeffe	erson St									
0.33	1700 To:	F	98%	1%			0%	0%	С	0.104	F		1700	F	2011
	From														
0.25	440	F	98%	1%	1%	0%	0%	0%	С	0.101	F		450	F	2011
	To:]	NCL Clifton	n Forge; ()3-606								
0.06		<u> </u>	09%	10/				09/		0.000	_		1000	_	2011
0.00	1900 To:		90 /6	1 /0			0 76	076	-	0.099			1900		2011
0.01	From:		000/	10/			00/	00/		0.101	_		2200	_	2011
0.21	2100		98%	1%			0%	0%		0.101	r		2200	г	2011
0.15	1700		99%	0%			0%	0%	С	0.100	F		1800	F	2011
0.10	To	·	0070	070									1000	•	2011
0.31	1300 From:	F	99%	0%	0%	0%	0%	0%	С	0.101	F		1400	F	2011
	To:				Ber	nton St									
0.09	1100	F	99%	0%	0%	0%	0%	0%	F	0.098	F		1100	F	2011
	From:														
1.15		F	98%	1%		0%	0%	0%	С	0.107	F		580	F	2011
	To					son Ave									
	From	L			Chu	urch St									
	1400 To:	F			TI	S 60				0.089	F		1400	F	2011
	From:														
		F			LIC 60 N	Join Ctuo	at			0.095	F		2500	F	2011
							et								
	150	F			31	iusi				0.141	F		150	F	2011
	To				2r	nd St									
	From:				Oak Hi	ll Avenu	e			0.400	_		000	_	0044
	280 To:	F			ECL Cli	ifton For	ge			0.120	F		280	F	2011
	From						O-								
	1600	G								NA			1600	G	2011
							'd								
		F			Rev	vere St				0.105	F		300	F	2011
	To:				I	[-64				3.100				•	2011
	From				Ing	alls St									
	570	F			T _C -1-	on Ctor				0.115	F		570	F	2011
	From:									<u> </u>					
	1100	F			U	D 00				0.097	F		1100	F	2011
	1100	•													
	To:				Chestr	nut Stree	t								
	From:	F				nut Stree	t			0.093	F		1100	F	2011
	0.05 0.34 0.12 0.33 0.25 0.06 0.21 0.15 0.31	0.05 290 Trom 0.34 80 To 0.12 1800 To From 0.33 1700 To 0.25 440 0.21 2100 0.15 1700 0.31 1300 0.09 1100 To From 1400 To From 1400 To From 150 To	0.05	0.05	Length AADT QA 4Tire Bus Bus	Company Comp	Length AADT QA 4Tire Bus Call Call	Dead End Dead End	Length AADT QA	Company Comp	Length AADT QA 4Tire Bus Carte Carte	Company Comp	Length AADT QA 4Tire Bus Truck Truck QC Factor QK Dir Factor CAM ATire Bus Truck QAM ATIRA ATIRA	Length AADT QA 4Tire Bus Truck 2Arde 34-Arde 1Trail 2Trail 2	Length AADT QA 4Tire Bus Cand 34-Alight 1Trail 2Trail 2Trail 2Trail Cand Rector Cand Rector Cand Ca

8/27/2012 10