2014

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 316

Town of Urbanna

Information in this report is included in Report

59

(Middlesex County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	


(F241)	Frontage Road (F precedes frontage route number)


(600) Secondary Route

Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

Virginia State Route





Virginia Department of Transportation Traffic Engineering Division 2014

Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

Route	Jurisdiction	Length I	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW
	From:	ECl	L Urbanna													
(227)	Town of Urbanna (Maint: 59)	0.63	3100	N	98%	0%	1%	1%	1%	0%	Ν	0.091	Ν	0.507	3100	Ν
	To:	WC	L Urbanna	ì												

4/21/2015 7

Virginia Department of Transportation Traffic Engineering Division 2014 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

						TOWIT	of Urbar	IIIa								
Route	Length	AADT	QA	4Tire	Bus		Trı 3+Axle		2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Urbanna																
(1001) Rappahannock Ave	0.33	770	G	98%	1%	1%	SR 227 0%	0%	0%	С	0.102	F	0.54	790	G	2014
(1001) Rappahannock Ave	0.33	770		30 /6	1 /0				0 /6	U	0.102	'	0.54	790	G	2014
(1001) Rappahannock Ave	0.14	390 From	G	92%	4%	59-1006 3%	Marston 1%	Ave 0%	0%	F	0.125	F	0.609	400	G	2014
(1001) Rappahannock Ave	0.14	390		J∠ /0	4 /0				0 /6	ı	0.123	'	0.009	400	G	2014
(1001) Rappahannock Ave	0.18	160	G	92%	4%	59-100 3%	7 Taylor <i>I</i> 1%	4ve 0%	0%	С	0.128	F	0.762	160	G	2014
(1001) Rappahannock Ave	0.10	100	_	JZ /6	4 /0)14 Kent S		0 76		0.120	'	0.702	100	ч	2014
		From	d				ead End									
(1002) Virginia St	0.23	250	R			D	cad Liid				NA			NA		05/26/2009
(1002) Virginia St		To				SR 22	27; 59-100)5								
		From	d			59-1009 P	rince Geo	orge St								
Prince George St	0.12	660	R								NA			NA		05/26/2009
59		To	c			5	SR 227									
<u> </u>		From	i:			D	ead End									
(1004) Wattling St	0.05	70	R								NA NA			NA		05/26/2009
<u> </u>		To					SR 227									
O 0 0:	0.05	From		000/	40/		SR 227	00/	00/			_	0.507	000		0014
(1005) Cross St	0.25	590	G	98%	1%	1%	0%	0%	0%	С	0.116	F	0.597	600	G	2014
<u> </u>		From					Marston									
(1005) Cross St	0.15	380	G	98%	1%	1%	0%	0%	0%	F	0.097	F	0.578	390	G	2014
<u> </u>		To From				59-100	7 Taylor A	Ave								
(1005) Cross St	0.09	180	R								NA			NA		05/26/2009
		To From				59-101	13 West A	ve			<u> </u>					
1005 Cross St	0.06	90	R								NA			NA		05/26/2009
59		To	c			59-1008	Colorado	Ave								
		From			5	9-1001 Ra	ppahanno	ck Ave								004.4
(1006) Marston Ave	0.10	230	G	98%	1%	0%	0%	0%	0%	С	0.161	F	0.59	230	G	2014
		To From				59-10	05 Cross	St								
(1006) Marston Ave	0.14	100	R								NA NA			NA		05/26/2009
<u> </u>		To				D	ead End									
O =		From			5	9-1001 Ra	appahanno	ock Ave			<u> </u>					.= //
Taylor Ave	0.10	60	R								NA			NA		05/26/2009
		From				59-10	05 Cross	St								
Taylor Ave	0.07	180	R								NA			NA		05/26/2009
		To	<u>'</u>				Chandler									
Calarada Aus	0.10	From	Щ_		5	9-1001 Ra	appahanno	ock Ave						NIA		05/07/000
(1008) Colorado Ave	0.13	60 To	R			50.10)14 Kent S	2+			NA			NA		05/27/2009
		From				59-1003 P										
(1009) Prince George St	0.04	900	R			39-1003 P	Tince Geo	ige si			NA			NA		05/26/2009
Prince George St	0.0 .	To	· · ·			5	SR 227									00/20/200
		From	ı			9	SR 227									
Grace Ave	0.05	490	R				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				NA			NA		05/27/2009
59		To	_			59-102	5 Hilliard	St								
(1010) Grace Ave	0.06	370 From	R			37 102	3 milara	. Dt			NA			NA		05/27/2009
Grace Ave		To	_			50.10)19 Park S	2+								
(1010) Grace Ave	0.08	240 From	R			J7-10	717 1 al K c	л			NA			NA		05/27/2009
(1010) Grace Ave		To	ı		_	59-102	20 Bonner	St		_						
		From	:				ead End				Ī					
1012 Howard St	0.30	190	R								NA			NA		05/27/2009
59		To	c			59-10	05 Cross	St								
_		From			5	9-1001 Ra	ıppahanno	ck Ave								<u> </u>
(1013) West Ave	0.17	60	R								NA			NA		05/27/2009
29		To	e e			50 10	14 Kent S	2+								

4/21/2015 8

Virginia Department of Transportation Traffic Engineering Division 2014 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Urbanna

							or orba								
Route	Length	AADT	QA	4Tire	Bus			ruck e 1Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Urbanna															
(1014) Kent St	0.10	50	R		5	9-1001 R	appahann	ock Ave		NA			NA		05/26/200
1014 Kent St	0.19	OU To:	n			59-10	013 West A	Ave					INA		03/20/200
		From:					SR 227	110		1					
1015 Watling St	0.11	130	R				SK 221			NA			NA		05/26/200
	· · · ·	To:				EC	L Urbann	a							00/20/200
		From					SR 227								
Upton Lane	0.04	550	R							NA			NA		05/27/200
		To:				Ι	Dead End								
<u> </u>		From:				Ι	Dead End								
Obert St	0.13	60	R							NA			NA		05/27/200
		To:			5	9-1001 R	appahann	ock Ave							
Park St		From:				59-10	21 Linder	n St							
	0.12	140	R							NA			NA		05/27/20
		10:			5		appahann	ock Ave							
Bonner St	0.05	From:				Ι	Dead End			<u>ا</u>			NIA		05/00/00
	0.05	180	R							NA			NA		05/29/20
		From				59-10	21 Linder	ı St							
Bonner St	0.12	190	R							<u>N</u> A			NA		05/27/20
		To:			5		appahann								
O 11 1 2		From:				59-1	019 Park	St		<u> </u>					. = /. = /
Linden St	0.14	80 To:	R				15.1			NA			NA		05/27/20
		10.					Dead End								
Chandler Ave	0.04	30	R			1	Dead End						NIA		05/06/00
1022 Chandler Ave	0.04	30	n							NA 			NA		05/26/20
		From				59-100	07 Taylor	Ave		<u> </u>					0=/00/00
Chandler Ave	0.05	100	R							NA			NA		05/26/20
							Dead End								
Uilliard Ct	0.06	From:				Ε	Dead End			NA			NA		05/24/20
Hilliard St	0.06	100 To:	R			50.10	10 Grace .	Ava		IVA			INA		03/24/20
		From:	ļ												
(1026) Red Cedar Lane	0.06	30	R		5	9-1001 R	appahann	ock Ave		NA			NA		05/24/20
Red Cedar Lane	0.00	To:	n			C	ul-de-Sac						INA		03/24/20
		From:			E			ools Asso							
Parkview Lane	0.06	80	R		3	9-1001 K	appahann	ock Ave		NA			NA		05/27/20
Parkview Lane	0.00	To:				C	ul-de-Sac								55,21,20
		From:			5		appahann	ock Ave		i					
1028 Manor Rd	0.12	100	R			, 1001 K	арранаш	OCK TIVE		NA			NA		05/27/200
59	-	To:				C	ul-de-Sac								. •

4/21/2015 9