2015

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 130

Town of South Boston

Information in this report is included in Report

41

(Halifax County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	

(F241)	Frontage Road (F precedes frontage route number)

(600) Secondary Route

Virginia State Route

Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

Virginia Department of Transportation Traffic Engineering Division 2015

Annual Average Daily Traffic Volume Estimates By Section of Route Town of South Boston

_			4T:	_		Tru		_	K	Dir			
Route	Jurisdiction	Length AADT QA	4Tire	Bus		3+Axle	-		QC	Factor	QK Factor	AAWDT	Q۱
	From:	North Main St	2221	4.51		061	051	061		0.000		0522	_
34 Hodges St	Town of South Boston	0.54 1900 G	98%	1%	1%	0%	0%	0%	С	0.099	0.556	2000	G
	100	US 360 John Randolph Bl											
(58) (360) Bill Tuck Hwy	Town of South Boston	US 501 Huell Matthews H 0.18 12000 G	85%	1%	1%	1%	12%	0%	F	0.077	0.549	13000	G
58 360 Bill Tuck Hwy	To:	ECL South Boston	00 70	1 /0	170	1 /0	12 /0	0 70	'	0.077	0.545	10000	
	From:	US 501 P; Wilborn Ave; Ma	in St										
129 North Main St	Town of South Boston	0.09 3300 G	99%	1%	0%	0%	0%	0%	F	0.090	0.799	3600	(
	To	US 501 Broad St											
North Main St	Town of South Boston	0.38 5400 G	99%	1%	0%	0%	0%	0%	С	0.094	0.586	5700	(
	To	SR 34 Hodges St											
129 North Main St	Town of South Boston	0.16 6400 G	99%	1%	0%	0%	0%	0%	F	0.095	0.51	6800	(
123)	Too	Edmunds St											
North Main St	From: Town of South Boston	0.19 6900 G	99%	1%	0%	0%	0%	0%	F	0.098	0.523	7300	(
123)	To												
North Main St	Town of South Boston	College St 0.63 6400 G	99%	1%	0%	0%	0%	0%	F	0.098	0.513	6800	(
129	Tol.		00,0	.,,		0,0	0,70	0,70	•	0.000	0.0.0	0000	
North Main St	Town of South Boston	Hamilton Blvd 0.88 11000 G	99%	1%	0%	0%	0%	0%	С	0.094	0.516	12000	(
129) 10101 111011 01	To:	NCL South Boston	0070	.,,		0,0	0,70	0 / 0	Ū	0.00	0.0.0	000	
	From:	US 501 P; Main St											
304)Seymour Dr	Town of South Boston	0.08 2800 G	95%	1%	1%	2%	1%	0%	F	0.091	0.603	3000	C
\smile	To	US 501 Broad St											
304 Seymour Dr	Town of South Boston	0.38 2900 G	95%	1%	1%	2%	1%	0%	С	0.100	0.516	3100	(
	To	Marshall St			<u> </u>								
304)Seymour Dr	Town of South Boston	0.25 2700 G	95%	1%	1%	2%	1%	0%	F	0.099	0.504	2900	
	То:	US 360 John Randolph Bl	vd										
	From:	US 501 Riverdale											
360 58 Bill Tuck Hwy	Town of South Boston	0.18 12000 G	85%	1%	1%	1%	12%	0%	F	0.077	0.549	13000	C
	To:	CL South Boston											
360 John Randolph Blvd	Town of South Boston (Maint: 41)	SCL South Boston 0.16 10000 G	86%	1%	1%	2%	11%	0%	F	0.084	0.518	10000	(
300)	To To			. , ,									_ `
360 John Randolph Blvd	Town of South Boston	SR 304 Seymour Dr 0.52 11000 G	86%	1%	1%	2%	11%	0%	F	0.081	0.673	11000	(
300)35 1 (4.140.)5.1 2.14	Tolling Tolling		0070	1 /3		_,0	11/3	0 / 0	•	3.001	0.070	11000	•
360 John Randolph Blvd	Town of South Boston	SR 34 Hodges St 0.44 12000 G	86%	1%	1%	2%	11%	0%	F	0.086	0.564	12000	(
360 36111 Haridolph Biva			00 /8	1 /0	1 /0	270	11/0	0 /0	'	0.000	0.504	12000	
360 John Randolph Blvd	Town of South Boston (Maint: 41)	<u>Hamilton Blvd</u> 0.09 8400 G	86%	1%	1%	2%	11%	0%	F	0.085	0.641	8400	
360 Journ Handolph Blvd	Town of South Doston (Maint. 41)	ECL South Boston	00%	1 70	1 70	∠70	1170	U 70	Г	0.000	0.041	0400	

5/3/2016 7

Virginia Department of Transportation Traffic Engineering Division 2015

Annual Average Daily Traffic Volume Estimates By Section of Route Town of South Boston

								K		Dir		- 014			
Route	Jurisdiction	on Length	AADT (QA 4Tir	e Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK	Factor	AAWDT	Q۱
~~~	From:		360; SCL South			10/	00/	00/	00/	-	0.000		0.54	10000	_
501 Main St	Town of South			<b>G</b> 86%	5 1%	1%	3%	9%	0%	F	0.088		0.54	19000	G
	From		501 P; Broad S 501 P Main St												
501 Broad St	Town of South			<b>G</b> 97%	6 0%	1%	0%	2%	0%	F	0.091		0.539	9600	(
901)	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	17000	<b>G</b> 97%	6 1%	1%	0%	2%	0%	F	0.091	F	0.767	18000	(
	To		304 Seymour D												
501 Broad St	Town of South			<b>G</b> 97%	6 0%	1%	0%	2%	0%	С	0.099			9000	(
301)=1000	Combined Traffic Estimates for 2 Parallel			<b>G</b> 97%		1%	0%	2%	0%	C	0.089	F	0.518	18000	(
	To To				. , ,		0 / 0	_,,	0,0	Ū	0.000	•	0.0.0	.0000	
501 Broad St	Town of South		29 North Main 6600	G 97%	6 0%	1%	0%	2%	0%	F	0.086			7000	(
501 Broad of	Combined Traffic Estimates for 2 Parallel			<b>G</b> 96%		1%	0%	2%	0%	F	0.09	F	0.511	15000	(
	Combined Traine Estimates for 21 arailer	rioadways on this riodle.		<b>G</b> 307	0 1/0	1 /0	0 /6	2/0	0 /6	'	0.03	•	0.511	13000	`
Drood Ctroot	Town of South	Boston 0.18	Third St	• 000	′ 10/	10/	10/	20/	00/		0.000			6000	
501 Broad Street				<b>G</b> 96%		1%	1%	2%	0%	С	0.088	_	0.50	6800	(
	Combined Traffic Estimates for 2 Parallel	Hoadways on this Houte:	16000	<b>G</b> 96%	6 1%	1%	0%	2%	0%	F	0.085	F	0.52	17000	(
~~	To:		Edmunds St												
501 Broad Street	Town of South			<b>G</b> 96%		1%	1%	2%	0%	F	0.087			6800	(
	Combined Traffic Estimates for 2 Parallel			<b>G</b> 96%	ú 1%	1%	0%	2%	0%	F	0.084	F	0.518	17000	(
	To:		01 P Wilborn A 501 P: Broad S												
501 Wilborn Ave	Town of South			<b>G</b> 96%	6 1%	1%	1%	2%	0%	F	0.093		0.502	16000	(
301)	To														
501 Halifax Rd	Town of South		amilton Blvd 16000	<b>G</b> 96%	6 1%	1%	1%	2%	0%	F	0.092		0.523	17000	(
501) Hamax Ha	Town of Court				0 170		1 /0	270	0 70	•	0.002		0.020	17000	`
501 Halifax Rd	Town of South		CL South Bost		6 1%	1%	1%	2%	0%	F	0.090		0.554	10000	(
501 Haillax Nu	Town of South	0.79	18000	<b>G</b> 96%	0 170	1 70	1 70	270	0%	Г	0.090		0.554	19000	(
~~~	Tor From:		N, Old Halifax							_					
501 Halifax Rd	Town of South			G 96%	ú 1%	1%	1%	2%	0%	F	0.089		0.54	21000	(
	10.		L South Boston	1											
Main Ct	Towns of Courts		501 Broad St	G 96%	′ 10/	10/	00/	00/	00/	_	0.001			0000	,
5β1 Main St	Town of South					1%	0%	2%	0%	-	0.091	_	0.707	8200	(
	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	17000	G 97%	6 1%	1%	0%	2%	0%	F	0.091	F	0.767	18000	(
<u></u>			304 Seymour D												
501 Main St	Town of South			G 96%		1%	0%	2%	0%	С	0.089			8500	(
	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	16000	G 97%	6 1%	1%	0%	2%	0%	С	0.089	F	0.518	18000	(
	To: From:	SR 12	29 North Main	St											
Wilborne Ave	Town of South	Boston 0.26	7900	G 96%	6 1%	1%	0%	2%	0%	F	0.09		0.901	8400	(
\frac{1}{2}	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	14000	G 96%	ú 1%	1%	0%	2%	0%	F	0.09	F	0.511	15000	(
	To		Third St												

Virginia Department of Transportation Traffic Engineering Division 2015

Annual Average Daily Traffic Volume Estimates By Section of Route Town of South Boston

Route	Jurisdiction Len	ngth	AADT	QA	4Tire	RIIS	2Axle				QC	K Factor	QK	Dir Factor	AAWDT	QW
Sp1 Wilborne Ave	Town of South Boston 0.5		Third St 9700	G	96%	1%	1%	0%	2%	0%	F	0.085		0.807	10000	G
	Combined Traffic Estimates for 2 Parallel Roadways on this Rou		16000 1 Broad Str	G reet	96%	1%	1%	0%	2%	0%	F	0.085	F	0.519	17000	G

Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route Town of South Boston

						lown of South Bos	ston							
Route	Length	AADT	QA	4Tire	Bus	Truc 2Axle 3+Axle 1			QC	K Factor	QK Dir Fact	$\Delta \Delta WDT$	QW	Year
Town of South Boston														
Dellused Ave	0.00	From	<u> </u>	070/	00/	Edmunds St	00/	00/			0.50	1 740	_	0015
1 Railroad Ave	0.36	690	G	97%	0%	1% 2%	0%	0%	С	0.104	0.58	1 740	G	2015
Deilyseed Assessed	0.10	From	┖	070/	00/	Summit Dr	00/	00/		0.000	0.00	0 010		0015
1 Railroad Avenue	0.18	860 To	G	97%	0%	1% 2% Seymour Dr	0%	0%	F	0.098	0.60	2 910	G	2015
		From				•				+				
2 Riley Ave	0.16	900	G	98%	1%	Seymour Dr 1% 0%	0%	0%	С	0.100	0.51	0 960	G	2015
2)	00	To	Ť		. , 0	Vaughan St	0 70	0,0			0.0.		.	_0.0
		From				Ferry St								
3 Seymour Dr	0.11	720	G	97%	0%	1% 2%	0%	0%	С	0.124	0.54	3 770	G	2015
		To				Watkins Ave								
		From				Riley Ave								
(4) Vaughan St	0.35	1000	G	98%	1%	1% 1%	0%	0%	С	0.099	0.53	9 1100	G	2015
<u> </u>		To	1			Pine Ave								
O W L	0.04	From	<u> </u>	070/	40/	Wilborn Ave	00/	20/			0.50		_	0045
5 Webster St	0.61	910 To	G	97%	1%	1% 1%	0%	0%	С	0.089	0.50	6 970	G	2015
		From	1			North Main St								
6 Third St	0.14	460	G	97%	1%	US 501; Broad St 1% 0%	1%	0%	С	0.125	0.66	0 490	G	2015
6 I hird St	0.14	400		31 /6	1 /0	1US 501-P Wilborn A		0 70		0.123	0.00	0 430	a	2013
		From				WCL South Boston				1				
4700) Berry Hill Rd	1.13	1800	G	98%	0%	1% 0%	0%	0%	С	0.098	0.52	1900	G	2015
,		To				Wilmoth Ave								
Berry Hill Rd	0.20	2700 From	G	98%	0%	1% 0%	0%	0%	F	0.089	0.52	7 2900	G	2015
4700) 2011) 1 1111 1 10	0.20			0070					•		0.02		.	_0.0
4700) Edmunds St	0.06	3000 From	G	98%	0%	Summit Dr 1% 0%	0%	0%	F	0.083	0.52	0 3200	G	2015
27/00) Lamanas St	0.00	- T-		0070	0 70		0 70	0 / 0		- 0.000 	0.02	0 0200	ď	2010
4700) Edmunds St	0.45	1900	G	98%	0%	Railroad Ave	0%	0%	С	0.086	0.55	3 2000	G	2015
Edmunds St	0.40	To	ŭ	3070	0 70	US 501; Wilborn Av		0 / 0		0.000	0.00	0 2000	ď	2010
		From				US 501 Wilborn Av								
4700) Edmunds St	0.54	1400	G	96%	1%	2% 1%	0%	0%	С	0.092	0.51	9 1500	G	2015
<u> </u>		To	1			SR 29; North Main S	St							
<u> </u>	0.45	From	<u> </u>	000/	40/	Seymour Dr	00/	20/			0.50	. 700	0	0045
Marshall Ave	0.15	720	G	98%	1%	1% 1%	0%	0%	F	0.183	0.50	9 760	G	2015
		From				Fenton St								
4701) Marshall Ave	0.41	820	G	98%	1%	1% 1%	0%	0%	С	0.127	0.5	880	G	2015
		10				Hodges St								
Llamilton Dlud	0.07	From	L	000/	00/	SCL South Boston		00/		0.005	0.57	0 0000	0	2015
4702 Hamilton Blvd	0.37	3000		99%	0%		0%	0%	С	0.095	0.57	8 3200	G	2015
		From				Wilborn Ave		221		<u> </u>				
4702 Hamilton Blvd	0.70	5700	G	93%	1%	1% 1%	4%	0%	С	0.105	0.52	1 6100	G	2015
<u> </u>		Te From				SR 129 North Main S								
4702 Hamilton Blvd	1.26	7800	G	95%	1%	1% 1%	3%	0%	С	0.109	0.58	2 8300	G	2015
					, L	JS 360 John Randolph	Blvd							
Oallana Ct	0.00	From	<u> </u>	000/	10/	North Main St	00/	00/			0.50	T 1100	_	0015
4704 College St	0.80	1000	G	99%	1%	0% 0% Cavalier Blvd	0%	0%	С	0.102	0.50	5 1100	G	2015
		From	1											
4710) Jeffress St	0.20	720	G	97%	1%	North Main St 1% 0%	0%	0%	С	0.105	0.59	2 770	G	2015
Jeffress St	0.20	. 20	Ť	J1 /0	1 /0	Fenton St	J /U	J /J		7.100	0.00	_ ,,,	G	2010
		From				Jeffress St								
Fenton St	0.19	470	G	99%	1%		0%	0%	С	0.111	0.71	9 510	G	2015
		To	1			Marshall Ave								
$\overline{}$		From				Edmunds St								
4713 Watkins Ave	0.61	1900	G	96%	1%		0%	0%	С	0.096	0.50	5 2000	G	2015
$\overline{}$		To	1			Seymour Dr								

Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route Town of South Boston

Route	Length	AADT	QA	4Tire	Bus	Truck2Axle 3+Axle 1Trail 2Trail	QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
wn of South Boston		From											
0 1 1 01						Watkins Ave		_					
Carrington St		NA						NA NA			NA		
		Tr				Noblin Ave							
		From				Llewellyn Avenue							
College St		500	G					0.100		0.626	500	G	201
	Tec Washington Avenue												
		From				Wilborn Ave							
Greenway Dr		360	G					0.109		0.738	360	G	201
<u> </u>		To				Norwood Ave							
		From				Spring Avenue							
Ridge St		290	G					0.124		0.622	290	G	201
		To				Alderson Avenue						G 2	
		From				Halifax Rd							
Robin Hood Rd		430	G					0.107		0.638	430	G	201
		To				Nottingham Dr							