### 2015

# Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

### Special Locality Report 139

Town of Wytheville

Information in this report is included in Report

98

(Wythe County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

#### Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

#### **Publication Notes**

#### Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

#### Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

#### QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

**2Axle Truck**: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

**3+Axle Truck**: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

### Route Shield Legend

#### Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	

(F241)	Frontage Road (F precedes frontage route number)

(600) Secondary Route

Virginia State Route

### Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wye - Wye Route connector

- P Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
- The VDOT Maintainenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Wytheville

							Tru	ck			K	Dir Dir		
Route	Jurisdiction	Length A	AADT Q	A 4Tire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK Factor	AAWDT	QW
~	From:		Wytheville											
(11) W Lee Hwy	Town of Wytheville	0.29	4200 I	98%	1%	0%	0%	1%	0%	С	0.106	0.644	4600	F
~	To: From:		24th St											
11) W Lee Hwy	Town of Wytheville		6200 I	98%	1%	0%	0%	1%	0%	F	0.099	0.571	6700	F
	From:		21 Main St 2th St											
(11) (21) Main St	Town of Wytheville		5600 F	98%	1%	0%	0%	1%	0%	F	0.089	0.579	6100	F
	To:		4th St											
Main Ct	From:		21, 4th St	000/	10/		00/	10/	00/	_	0.004	0.540	7400	_
11 Main St	Town of Wytheville	0.33	6800 I	98%	1%	0%	0%	1%	0%	F	0.084	0.546	7400	F
~~	From:		5th St			<u> </u>				_				
(11) Main St	Town of Wytheville	0.20 <b>6</b>	6800 I	98%	0%	1%	0%	1%	0%	F	0.083	0.523	7400	F
<del>*</del>	To: From:		1th St											
(11) E Main St	Town of Wytheville	0.50	9700 I	98%	0%	1%	0%	1%	0%	С	0.085	0.522	11000	F
<u> </u>	To: From:	Lil	berty St			$\Box$ $\vdash$								
11 E Main St	Town of Wytheville	0.78 <b>8</b>	8800 I	98%	0%	1%	0%	1%	0%	F	0.089	0.578	9600	F
$\bigcirc$	To	139-3	3 Lithia Rd			<u> </u>								
11 E Main St	Town of Wytheville (Maint: 98)			98%	0%	1%	0%	1%	0%	Ν	0.089	0.578	9600	Ν
	To:		I-81											
~ ~ P		00011-P(U)/US-0001	11-N072A(R											
(11) (11) Ramp to I-81 N at Exit 73	Town of Wytheville (Maint: 98)	0.27 00081-N(R)/US-000	11 NO72 A (D			1 for dir	ectional t	raffic v	olume e	stima	tes for thi	s segment.		
	From:		I-81	// FROM KI	11									
(11) (81) (77) (52)	Town of Wytheville (Maint: 98)	0.96		S	See I-81	for dire	ctional tr	affic vo	lume es	timate	es for this	segment.		
Combined Tr	raffic Estimates for 2 Parallel Roadways o	n this Route: 5	2000 (	74%	1%	1%	1%	22%	2%	С	0.115	A 0.601	48000	G
	Τα	NCL '	Wytheville											
North	From:	Ţ	US 11											
Ramp to I-81 N at Exit 73	Town of Wytheville (Maint: 98)	0.27	3400 I								0.097		3400	F
$\bigcirc$	To:	I	I-81 N											
North	From:		US 11											
(11) Ramp to I-81 S at Exit 73	Town of Wytheville (Maint: 98)		1200 I								0.084		1200	F
<u> </u>	To:	I	I-81 S											
~~~ a	From:		Wytheville											_
(21) Grayson St	Town of Wytheville		4100 F	98%	0%	1%	1%	1%	0%	С	0.097	0.636	4400	F
~	From:		Main St ayson St											
121 Main St	Town of Wytheville		6100 I	98%	0%	1%	1%	1%	0%	F	0.093	0.647	6600	F
	Tα		Lee Hwy; 12t											
~ ~	From:		Hwy; 12th St											
(21) (11) Main St	Town of Wytheville		5600 I	98%	1%	0%	0%	1%	0%	F	0.089	0.579	6100	F
<del></del>	To: From:		h Street 1 Main St											
(21) 4th St	Town of Wytheville		3000 I	98%	0%	0%	0%	1%	0%	F	0.086	0.537	14000	F

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Wytheville

			- •					Tri	ıck			K		Dir		
Route	Jurisdictio	on Length	AADT	QA	4Tire	Bus		3+Axle	-		QC	Factor	QK	Factor	AAWDT	QW
21) 4th St	Town of Wyth	neville 0.40	W Ridge Rd 14000	F	98%	0%	0%	0%	1%	0%	С	0.092		0.506	15000	F
21) 4th St	Town of Wyth	neville 0.12	Tazewell St <b>15000</b> I-81; US 52	F	98%	0%	0%	0%	1%	0%	F	0.078		0.502	16000	F
(52) (81) (77) (11)	From: Town of Wytheville	(Maint: 98) 0.93	US 11		Se	ee I-81	for dire	ctional t	raffic vo	lume es	timate	es for this	sear	nent.		
	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	52000 ICL Wythevil	<b>G</b> lle	74%	1%	1%	1%	22%	2%	С	0.115	Α	0.601	48000	G
52 81 77	Town of Wytheville	,	US 11								timate	es for this	_			
	Combined Traffic Estimates for 2 Parallel		US 11	G	74%	1%	1%	1%	22%	2%	F	0.113	A	0.549	44000	G
[52] [81]	Town of Wytheville Combined Traffic Estimates for 2 Parallel $$^{\rm Tox}$$	Roadways on this Route:	27000 -77 Wythevil	G	80%	ee I-81 1 1%	for dire 1%	ctional t 1%	raffic vo 17%	lume es 1%	timate F	es for this 0.099	s segr A	nent. 0.649	26000	G
52 81 Ramp I-81 S Exit 7	70 to US 21; US 58 Town of Wytheville		US 11				for dire	ctional t	raffic vo	lume es	timate	es for this	segr	ment.		
52) 4th St	From: Town of Wyth To	Maneville 1.89	aintenance Br 2400 /CL Wythevi	reak <b>F</b>	98%	0%	1%	1%	1%	0%	С	0.095		0.518	2700	F
(52) Ramp to I-81 N at Exit 7	Town of Wytheville		US 21; US 58 <b>4200</b>									0.092			4200	G
(52) Ramp to I-81 S at Exit 70	7 Town of Wytheville		I-81 N US 21; US 58 <b>1900</b>	8 <b>G</b>								0.089			1900	G
North South	To:	:	I-81 S ICL Wythevil	lle												
77 81 11 52	Town of Wytheville Combined Traffic Estimates for 2 Parallel	,	25000 52000	G G	75% 74%	1% 1%	1% 1%	1% 1%	21% 22%	2% 2%	C C	0.121 0.115	Α	0.601	24000 48000	G G
North South $(52)$	Town of Wytheville	(Maint: 98) 1.29	US 11 <b>24000</b>	Α	75%	1%	1%	1%	21%	2%	F	0.125			22000	A
(77) (81) (52)	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:		G	74%	1%	1%	1%	22%	2%	F	0.113	Α	0.549	44000	G
North 77 Ramp I-81 S Exit 72 to I-	•	(Maint: 98) 0.28	I-81 South 11000	F	77%	1%	1%	1%	19%	1%	F	0.082			9900	F
North	Combined Traffic Estimates for 2 Parallel		I-77 North -81 Wythevil	G	77%	1%	1%	1%	19%	1%	F	0.070	F	0.554	19000	G
North 77	Town of Wytheville Combined Traffic Estimates for 2 Parallel	(Maint: 98) 0.31	14000	A A	77% 77%	1% 1%	1% 1%	1% 1%	19% 19%	1% 1%	F F	0.150 0.138	Α	0.518	12000 25000	A A
	To:		eppers Ferry		,5	.,.	Ť	. , 5	, , ,	. , •	•	300		3.0.0		

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Wytheville

								Tru	ck			K		Dir		
Route	Jurisdictio	on Length	AADT	QA	4Tire	Bus		3+Axle	_		QC	Factor	QK	Factor	AAWDT	QW
North	From:		eppers Ferry													
(77)	Town of Wytheville	(Maint: 98) 0.23	14000	Α	77%	1%	1%	1%	19%	1%	F	0.138			13000	Α
	Combined Traffic Estimates for 2 Parallel			Α	77%	1%	1%	1%	19%	1%	F	0.13	Α	0.628	26000	Α
	To	N	ICL Wythevi	ille												
North	From:	:	I-77 North													
(77) Ramp	Town of Wytheville		1800	G								0.114			1800	G
	To	Pe	eppers Ferry	Rd												
South North	From:		ICL Wythevi		===/											
(77) (81) (11) (52)	Town of Wytheville	'	27000	Α	73%	1%	1%	1%	23%	2%	С	0.121			25000	Α
~ ~ ~	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	52000	G	74%	1%	1%	1%	22%	2%	С	0.115	Α	0.601	48000	G
South North			US 11													
(77) $(81)$ $(52)$	Town of Wytheville	(Maint: 98) 0.82	24000	G	73%	1%	1%	1%	23%	2%	F	0.116			22000	G
(1) (61) (52)	Combined Traffic Estimates for 2 Parallel	,		G	74%	1%	1%	1%	22%	2%	F	0.113	Α	0.549	44000	G
	To:		-81 Wythevi		7 1 70	170	Ť	1,70	/0	270	•	0.110	,,	0.010	11000	ŭ
South	From		I-81 N													
(77) Ramp I-77 S Exit 40 to	o 81 N Exit 72 Town of Wytheville	(Maint: 98) 0.66	11000	G	78%	1%	1%	1%	19%	1%	F	0.073			9600	G
$\smile$	Combined Traffic Estimates for 2 Parallel	Roadways on this Route:	22000	G	77%	1%	1%	1%	19%	1%	F	0.070	F	0.554	19000	G
	To		I-77 S													
South $77$	Town of Wytheville		-81 Wythevi 14000	A A	78%	1%	1%	1%	19%	1%	_	0.140			13000	Α
(1)	Combined Traffic Estimates for 2 Parallel	,		A	77%	1%	1%	1%	19%	1%	'	0.140	Α	0.518	25000	A
	Combined Trainic Estimates for 2 Faraner		ICL Wythevi		1170	1 70	170	1 70	1970	1 70	Г	0.136	А	0.516	23000	A
Oth-	From		I-77 S	me			1									
South Ramp From I-77 S Ex	tit 40 to I-81 S at Exit 72 Town of Wytheville	(Maint: 98) 0.22	2700	G	78%	1%	1%	1%	19%	1%	F	0.098			2400	G
77) Hamp Hom 177 G Ex	To	(Want. 50) 0.22	I-81 S		7070	1 /0		1 70	10 /0	1 /0	•	0.000			2400	ď
Courth	From		I-77 South													
South (77) Ramp	Town of Wytheville	(Maint: 98) 0.33	2300	G								0.09			2300	G
(11) Hamp	To	(	7 South Exit									0.00			2000	ŭ
South	From	I-77-S	041B FROM	1 RT 77												
(77) Ramp	Town of Wytheville	(Maint: 98) 0.03	NA									NA			NA	
$\overline{}$	To	139-5	5258 FROM	RT 77												
South	From:		041A FROM	1 RT 77												
(77) Ramp	Town of Wytheville	(Maint: 98) 0.05	NA									NA			NA	
$\overline{}$	To	139-5	5258 FROM	RT 77												
North	From		CL Wythevi													
81	Town of Wytheville	(Maint: 98) 2.03	12000	G	79%	1%	1%	1%	18%	1%	F	0.104			13000	G
$\smile$	Combined Traffic Estimates for 2 Parallel			G	80%	1%	1%	1%	17%	1%	F	0.095	F	0.533	25000	G
N. d	To		US 52, N F													
North	Town of Wytheville		21, N Fourt		709/	1%	10/	10/	100/	10/	_	0.116			15000	۸
81 52	•	,	15000	A	79%		1%	1%	18%	1%		0.116		0.040	15000	A
	Combined Traffic Estimates for 2 Parallel			G	80%	1%	1%	1%	17%	1%	F	0.099	Α	0.649	26000	G
	10	<u> </u>	-77 Wythevi	iie												

#### Annual Average Daily Traffic Volume Estimates By Section of Route Town of Wytheville

					4	_		Tru	ıck			K	011	Dir		
Route	Jurisdictio	on Length	AADT	QA	4Tire	Bus		3+Axle			QC	Factor	QK	Factor	AAWDT	QW
North North	From:		-77 Wythevi													
(81)     (77)     (52)	Town of Wytheville	'	24000	G	73%	1%	1%	1%	23%	2%	F	0.116			22000	G
~ ~ ~	Combined Traffic Estimates for 2 Parallel	Roadways on this Route	47000	G	74%	1%	1%	1%	22%	2%	F	0.113	Α	0.549	44000	G
North North	T <sub>O</sub> : From:	U	S 11, E Mair	n St												
(81) $(77)$ $(11)$ $(52)$	Town of Wytheville	(Maint: 98) 0.96	27000	Α	73%	1%	1%	1%	23%	2%	С	0.121			25000	Α
	Combined Traffic Estimates for 2 Parallel	Roadways on this Route	52000	G	74%	1%	1%	1%	22%	2%	С	0.115	Α	0.601	48000	G
	To:	N	ICL Wythevi	ille												
North	From:		I-81 N													
(81) Ramp I-81 N Exit 70 t	to US 21; US 58 Town of Wytheville	,	2200	G								0.091			2200	G
	To:		US 21; US 5	58												
North	From:		I-81 North													
(81) Ramp From I-81 N Ex	xit 72 to I-77 N at Exit 40 Town of Wytheville	(Maint: 98) 0.54	2600	F	77%	1%	1%	1%	19%	1%	F	0.09			2200	F
	To:		I-77 North													
North	From:		I-81 North													
(81) Ramp I-81 N Exit 73 t	to US 11 Town of Wytheville	(Maint: 98) 0.11	1200	G								0.092			1200	G
	10:		US 11													
South 81	From:		CL Wythevi		010/	10/	10/	10/	150/	10/	_	0.000			10000	_
81)	Town of Wytheville		12000	G	81%	1%	1%	1%	15%	1%	F	0.088	_	0.500	12000	G
	Combined Traffic Estimates for 2 Parallel		: US 52, N F	G Courth St	80%	1%	1%	1%	17%	1%	г	0.095	г	0.533	25000	G
South	From:		32, N Fourt													
(81) (52)	Town of Wytheville	(Maint: 98) 1.99	12000	G	81%	1%	1%	1%	15%	1%	F	0.105			12000	G
$\circ$	Combined Traffic Estimates for 2 Parallel	Roadways on this Route	27000	G	80%	1%	1%	1%	17%	1%	F	0.099	Α	0.649	26000	G
	Ter	ĭ	-77 Wythevi	lle			$\neg$ $\vdash$									
South North	Town of Wytheville		24000		75%	1%	1%	1%	21%	2%	_	0.125			22000	Α
81 77 52	Combined Traffic Estimates for 2 Parallel	'		A G	75% 74%	1%	1%	1%	22%	2%	F	0.123	Α	0.549	44000	G
	Combined Trainic Estimates for 2 Faraner	•			7470	1 /0	1 /0	1 /0	ZZ /0	2/0	'	0.113	^	0.549	44000	G
South North	To:	U	S 11, E Mair	n St												
(81) $(77)$ $(11)$ $(52)$	Town of Wytheville	(Maint: 98) 0.93	25000	G	75%	1%	1%	1%	21%	2%	С	0.121			24000	G
$\circ \circ \circ \circ$	Combined Traffic Estimates for 2 Parallel	Roadways on this Route	52000	G	74%	1%	1%	1%	22%	2%	С	0.115	Α	0.601	48000	G
	To:	N	ICL Wythevi	ille												
South	From:		I-81 South													
(81) (52) Ramp I-81 S Ex	xit 70 to US 21; US 58 Town of Wytheville		3400	G								0.1			3400	G
$\overline{}$	To:		US 21; US 5	58												
South	From:		I-81 South													
81 Ramp I-81 S Exit 73 t	to US 11 Town of Wytheville	(Maint: 98) 0.35	3700	G								0.110			3700	G
<u> </u>	To:		US 11													

# Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Wytheville

						1 OWIT OF	r Wythev	riiic								
Route	Length	AADT	QA	4Tire	Bus		Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
Town of Wytheville		From	Г			De	ad End									
(F36)	0.21	0	R				au Liiu				NA			NA		09/11/201
		To			1	39-5258 P	eppers Fer	ry Rd								
O		From:	L				osi Way									
(F41) Nye Rd	0.84	1700	F	88%	1%	1%	1%	9%	1%	С	0.134		0.573	1800	F	2015
		From	<u> </u>				Lovers Lar									
Factory Outlet Dr	1.36	2700	R		(	Connector 1	From US 1	1 NB			 NA			NA		09/05/201
(F42) 1 dolory odliot 51	1.00	To	r ii			ECL '	Wytheville	:			— T					00/00/201
		From:					Lovers Lar									
(F43) Lovers Lane	0.87	2200	R								NA			NA		09/07/201
$\bigcirc$		To				NCL '	Wytheville	;								
<u> </u>		From:					Lithia Rd									
(F324) Lithia Rd	0.48	1400	F	96%	1%	1%	0%	2%	0%	С	0.102		0.616	1500	F	2015
		10.					, E Main S	t								
1 Fairview Rd	1.19	1100	F	99%	0%	1%	2 N 4th St 0%	0%	0%	F	0.083		0.639	1200	F	2015
1 Fairview Rd	1.10	To	Ė	0070	0 70		Wytheville		0 70	•			0.000	1200	•	2010
		From					52 4th St									
2 Holston Rd	1.24	2700	F	99%	0%	1%	0%	0%	0%	F	0.085		0.537	2900	F	2015
		To				Co	ove Rd									
		From:				FR-41	Lithia Rd									
(4) Nye Rd	0.96	1900	F	99%	0%	1%	0%	0%	0%	F	0.073		0.506	2100	F	2015
<u> </u>		To					rs Ferry Ro									
Old Chana Dd	1.00	From	F	000/	00/		Wytheville		00/				0.000	1000	_	0015
(5250) Old Stage Rd	1.63	1200 <sub>то</sub>		99%	0%	1%	0% Grayson S	0%	0%	F	0.099		0.682	1300	F	2015
		From:					unia Rd									
(5252) W Ridge St	1.55	960	F	99%	0%	1%	0%	0%	0%	С	0.102		0.555	1000	F	2015
(0202)		To					8th St									
(5252) W Ridge Rd	0.49	1800 From:	F	99%	0%	1%	0%	0%	0%	F	0.098		0.503	1900	F	2015
		To				US	21 4th St									
		From				US 1	1 Main St									
(5253) Withers Rd	0.25	3000	F	98%	0%	1%	1%	0%	0%	F	0.092		0.527	3300	F	2015
<u> </u>		To: From:					1th St thers St									
(5253) 11th St	0.31	1700	F	98%	0%	1%	1%	0%	0%	С	0.1		0.524	1800	F	2015
(0200)		To					1 Main St									
(5253) 11th St	0.07	6300 From:	F	98%	0%	1%	1%	0%	0%	F	0.089		0.508	6800	F	2015
(3233)		To	_													
(5253) North St	0.12	2000 From:	F	98%	0%	1%	nroe St 1%	0%	0%	F	0.098		0.656	2200	F	2015
(3233)		To					sher Rd									
O 5: 1 - D 1	0.14	From		000/	00/		orth St	00/	201				0.000	4 400	_	0015
<sub>5253</sub> Fisher Rd	0.14	1300 To:	F	98%	0%	1%	1%	0%	0%	F	0.102		0.626	1400	F	2015
		From					Pine St	1								
(5255) Cove Rd	0.52	2700	F	98%	0%	1%	rs Ferry Ro	0%	0%	С	0.087		0.561	3000	F	2015
(5255) Cove Rd	5.52	т	·	0070	- 70			0 /0	<b>0</b> /0		<del></del>		0.001	3300	•	_0.0
(5255) Cove Rd	0.32	1300 From	F	98%	0%	1%	lston Rd 1%	0%	0%	F	0.097		0.55	1400	F	2015
(5255) Cove Rd	0.02	т	·	3070	3 /0			3,0	3,0	•			3.00		•	_0.0
(5255) Cove Rd	0.29	650 From:	F	98%	0%	Wyth	neview Dr 1%	0%	0%	F	0.096		0.736	710	F	2015
(5255) Cove Rd		To:	Ė	JU /0	J 70		Wytheville		J /0					, 10		
		From					2th St									
(5256) Spring St	0.30	1400	F	98%	0%	1%	1%	0%	0%	F	0.107		0.727	1500	F	2015
$\bigcirc$		To			_		4th St									

# Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Wytheville

						I own of V	Wytheville							
Route	Length	AADT	QA	4Tire	Bus		Truck +Axle 1Tra		QC	K Factor	QK Dir Facto	AAWDT	QW	Year
Town of Wytheville														
0.000	0.54	From	ᄂ	000/	00/		St Ook	00/			0.000	4000	_	0045
5256 Spring St	0.54	1400	F	98%	0%	1%	1% 0% h St	0%	F	0.1	0.606	1600	F	2015
		Fron								_				
5257 Tazewell St	0.06	1500	`	98%	0%	1%	in St 1% 0%	0%	F	0.108	0.570	1600	F	2015
(5257) Tazewell St	0.06	1300 To	┲	90%	076		roe St	0%	Г	0.108	0.570	1600	г	2013
		From								_				
5258 Monroe St	0.31	3000	F	98%	0%	12th St	0% 1%	0%	F	0.105	0.513	3300	F	2015
Monroe St	0.01	To	<u> </u>	30 70	0 70	4th St		0 70		-0.103	0.515	0000	•	2013
_		Fron					4th St							
5258 Monroe St	0.19	5500	F	98%	0%	1%	0% 1%	0%	F	0.102	0.564	6000	F	2015
$\bigcirc$		To	c				Street							
5258 Monroe St	0.15	5500	`L	98%	0%	1%	Street 1%	0%	F	0.095	0.544	6000	F	2015
Monroe St	0.13	<b>3300</b>	┲	30 /6	0 /6		th St	0 /6	- 1	0.093	0.544	0000		2013
		Fron	:				ı St							
5258) Monroe St	0.19	5500	F	98%	0%	1%	0% 1%	0%	F	0.094	0.556	6000	F	2015
$\cup$		Te				11+	h St							
5258) Peppers Ferry Rd	0.46	6500 From	F	98%	0%	1%	0% 1%	0%	С	0.087	0.509	7100	F	2015
<u> </u>		т.												
5258) Peppers Ferry Rd	0.59	5900	<u>.</u> F	98%	0%	Cov 1%	e Rd 0% 1%	0%	F	0.09	0.519	6400	F	2015
Peppers Ferry Rd	0.55	3300		30 70	0 70			0 70		0.00	0.515	0400	•	2013
	0.04	From		000/	00/	Ramp fr		00/			0.500	0400	N.I.	
Peppers Ferry Rd	0.21	2800	N	98%	0%	1%	0% 1%	0%	Ν	0.099	0.562	3100	N	2015
<u> </u>		Fron				Ramp								
Peppers Ferry Rd	0.53	2800	F	98%	0%	1%	0% 1%	0%	F	0.099	0.562	3100	F	2015
<u> </u>		To	1			ECL W	ytheville							
<u> </u>		Fron	<u> </u>			Peppers	Ferry Rd						_	
<sub>5258</sub> Ramp	0.29	2600	G							0.066		2600	G	2015
<u> </u>		To				I-77								
□ 5     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □     □	0.40	Fron				Peppers	Ferry Rd					2022		0045
<sub>5258</sub> Ramp	0.18	2300	G			Y 77	vy			0.091		2300	G	2015
			1			I-77								
4011-01	0.00	Fron	<u> </u>	000/	00/	Main S		00/			0.540	0000	_	0045
5260 12th St	0.29	2100	F	98%	0%	0%	0% 0%	0%	F	0.111	0.548	2300	F	2015
		Fron					on St h St			+				
5260) Union St	0.30	1800	F	98%	0%	0%	0% 0%	0%	F	0.116	0.51	2000	F	2015
		Te					n St							
5260) Withers St	0.56	2500 From	<u>Т</u>	98%	0%	0%	0% 0%	0%	С	0.094	0.526	2800	F	2015
(5260) Withers St	0.00	т		3070	3 /0		h St	0 /0			3.020		•	2010
		Fron	4				hall St							
5261) 4th St	0.31	2000	F	96%	1%	1%	1% 1%	0%	F	0.11	0.58	2200	F	2015
0_0,			·	/ •				- 70	-		0.00		-	_2.3
5261) 4th St	0.30	2000 From	<u>†</u> F	96%	1%	1%	ers St 1% 1%	0%	F	0.103	0.534	2100	F	2015
(5261) 4th St	0.30	ZUUU Ta		JU 70	1 /0	US 11		U 70	1"	0.103	0.534	- Z100	1	2013
		Fron	<u>.                                    </u>							<u> </u>				
5262) Marshall St	0.91	1400	F	96%	1%	1%	1% 1%	0%	С	0.112	0.598	1500	F	2015
Marshall St	0.91	To To		JU 70	1 /0	Main S		U 70	U	0.112	0.098	1300	1	2013
		From												
5264) Pine St	0.38	3700	`	99%	0%		e Highway 0% 0%	0%	С	0.095	0.549	4000	F	2015
Pine St	0.30	3700		JJ 70	U /0			U 70	U	0.095	0.549	4000	1	2013
O B' - G'	<u> </u>	Fron		0000			4th St				= :			
<sub>5264</sub> Pine St	0.44	390	F	99%	0%	0%	0% 0%	0%	F	0.118	0.6	420	F	2015
<u> </u>		To	<u> </u>				er Rd							
1011 5:		Fron				Frankli	n Street							
10th St		140	G							0.163	0.512	140	G	2015
		To	1			Washing	ton Street							

# Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route Town of Wytheville

Route	Length	AADT	QA	4Tire	Bus		True 3+Axle	_		QC	K Factor	QK	Dir Factor	AAWDT	QW	Yea
own of Wytheville		From														
							Spring St								_	
16th St		100	G								0.126		0.677	110	G	2015
		To				I	Franklin St									
		From				R	idge Street									
3rd St		370	G								0.164		0.546	370	G	2015
		To				Res	servoir Stree	t								
		From									<del></del>					
Church Ct			L			W	ashington St				0 1 4 2		0.616	700	F	201
Church St		670	<u> </u>								0.143		0.616	730	Г	201
		10	1			'	Withers St									
		From					11th St									
Mountain View Dr		730	F								0.109		0.579	790	F	201
		To					13th St									
		From					5th St									
Spiller St		130	F				Jui St				0.167		0.721	140	F	201
Spiller St		130					2.10				0.107		0.721	140	'	201
		10	1				3rd St									
		From					US 21	•		•						
Tazewell St		2800	G	99%	1%	0%	0%	0%	0%	С	0.102		0.606	2800	G	2015
		To				U	mberger St									