2015

Virginia Department of Transportation Daily Traffic Volume Estimates Including Vehicle Classification Estimates

where available

Special Locality Report 146

City of Norton

Information in this report is included in Report

97

(Wise County)

Prepared By

Virginia Department of Transportation Traffic Engineering Division

In Cooperation With

U.S. Department of Transportation Federal Highway Administration

Virginia Department of Transportation Traffic Engineering Division Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1 Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

North 81	Interstate Route	Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
29	US Route	


(F241)	Frontage Road (F precedes frontage route number)


(600) Secondary Route

Special Routes

Bus	Bus - Business Route
[29]	Bypas - Bypass Route
	Truck - Truck Route
ALT	ALT - Alternate Route
(220)	Wve - Wve Route connector

Virginia State Route





Virginia Department of Transportation Traffic Engineering Division 2015

Annual Average Daily Traffic Volume Estimates By Section of Route City of Norton

						_		Trι	ıck			K	Dir Dir		
Route	Jurisdiction	Length	AADT	QA	41 ire	Bus	2Axle	3+Axle	1Trail	2Trail	QC	Factor	QK Factor	AAWDT	QW
ALT	City of Norton (Maint: 97)	1.03	WCL Norton	G	94%	0%	1%	0%	5%	0%	F	0.087	0.541	15000	G
[23] [58]	City of Norton (Maint. 97)				94%	076	1 70	0%	3%	0%	Г	0.067	0.341	15000	G
ALT	From:		h St; 12th St E												
23 58 Orby Cantrell Hwy	City of Norton (Maint: 97)	1.50	16000	F	93%	0%	1%	1%	5%	0%	С	0.088	0.517	16000	F
Orbert Countriell I have	City of Northern (Majorty 07)	ALT US 58, SI				00/		00/	F0/	00/	F	0.000	0.505	01000	
Orby Cantrell Hwy	City of Norton (Maint: 97)	0.74	20000 NCL Norton	G	94%	0%	1%	0%	5%	0%	г	0.082	0.525	21000	G
North	From:		US 23												
	283, Alt US 58City of Norton (Maint: 97)	0.21		G								0.094		3000	G
*	To:		US 23; Gap												
Bus	From:		SCL Norton												
Park Ave	City of Norton	0.59	4200	F	95%	0%	1%	1%	3%	0%	F	0.090	0.513	4600	F
Bus	To: From:		15th Street												
23 Park Ave	City of Norton	0.56	8000	F	95%	0%	1%	1%	3%	0%	F	0.086	0.599	8700	F
Due	T _{cc} From:		11th St												
Bus 23 Park Ave	City of Norton	0.33	7300	F	95%	0%	1%	1%	3%	0%	F	0.087	0.545	7900	F
Bus	To: From:		8th St												
23 Park Ave	City of Norton	0.34	8200	F	95%	0%	1%	1%	3%	0%	F	0.087	0.519	8900	F
Bus	To: From:	SR	74 Coeburn Re	d											
23 Park Ave	City of Norton	0.26	10000	F	95%	0%	1%	1%	3%	0%	F	0.091	0.533	11000	F
~	To:		23, SR 283; Pa		e										
Bus 23 Park Ave	City of Norton	1.46	S US 23, SR 28 3600	83 F	98%	0%	0%	0%	1%	0%	F	0.094	0.531	3900	F
23) I alk Ave	Oity of Norton	1.40		-	30 /6	0 /6	U /0	0 /6	1 /0	0 /6	•	0.034	0.551	3900	
Bus	From		12th St NE	_											
Park Ave	City of Norton	0.04	NCL Norton	F	98%	0%	0%	0%	1%	0%	F	0.107	0.531	4500	F
ALT	From		WCL Norton												
58) (23)	City of Norton (Maint: 97)	1.03		G	94%	0%	1%	0%	5%	0%	F	0.087	0.541	15000	G
\sim	То		11th St												
ALT	From:	1.50		F	000/	00/	10/	10/	F0/	00/	_	0.000	0.517	10000	F
58 23 Orby Cantrell Hwy	City of Norton (Maint: 97)	1.50	16000	Г	93%	0%	1%	1%	5%	0%	С	0.088	0.517	16000	Г
ALT	To: From:		US 23												
Norton Coeburn Rd	City of Norton (Maint: 97)	1.06	11000	F	93%	1%	1%	1%	5%	0%	С	0.08	0.569	12000	F
~	To		ise County Line	e											
ALT (50)	City of Norton (Maint: 97)	1.03	14000	G	94%	0%	1%	0%	5%	0%	F	0.087	0.541	15000	G
(58) (23)	To		'h St; 12th St E		J4 /0	U /o	1 /0	U /o	J /0	U /o	'	0.007	0.541	13000	G

5/3/2016 7

Virginia Department of Transportation Traffic Engineering Division 2015

Annual Average Daily Traffic Volume Estimates By Section of Route City of Norton

Route	Jurisdiction	l enath	AADT	QA	4Tire	Bus		Truck			QC	K	QK	Dir	AAWDT	OW
rioute	dungalotion	Longin	ו מאא	QA.	71110	Dus	2Axle	e 3+Axle	1Trail	2Trail	QU	Factor	QIV	Factor	AAWDI	QVV
ALT	From:	11T	h St; 12th S	t Ext												
(58) (23) Orby Cantrell Hwy	City of Norton (Maint: 97)	1.50	16000	F	93%	0%	1%	1%	5%	0%	С	0.088		0.517	16000	F
	To:	ALT US 58, SR	283 Norto	n-Coebu	rn Hwy											
ALT ALT	From:	SR 283 A1US	58-P TO R	ΓE 23 S	OUTH											
(58) (58) Ramp	City of Norton (Maint: 97)	0.19			See	Alt US	58 for	direction	al traffic	volume	estim	ates for	this se	gment.		
	To:	US 23 FRO	OM ALT R	ΓE 58; 2	83											
ALT	From:	SR 283 A1US	58-P TO R	ΓΕ 23 S	OUTH											
8 Ramp	City of Norton (Maint: 97)	0.19	2300	G								0.101			2300	G
	To:	US 23	Orby Cantre	ell Hwy												
	From:		Park Ave													
74 Coeburn Ave	City of Norton	0.45	2300	F	99%	0%	1%	0%	0%	0%	С	0.101		0.512	2500	F
	To:	K	Lentucky Av	re												
	From:		Coeburn Rd													
74 Kentucky Ave	City of Norton	1.32	1000	F	97%	0%	1%	2%	1%	0%	F	0.098		0.591	1100	F
\bigcirc	To		12th St													
- Kentuaky Ava	City of Norton	0.39	12th St	F	97%	0%	1%	2%	1%	0%	С	0.091		0.525	1300	F
(74) Kentucky Ave	City of Norton			•	9770	0%	170	270	1 70	0%	C	0.091		0.525	1300	Г
	10.		ECL Nortor	1												
	From:		Bus US 23		•			•	•	•	•			•		•
$(_{283})$ Trail of the Lonesome Pine	City of Norton (Maint: 97)	0.36	11000	F	99%	0%	0%	0%	0%	0%	С	0.09		0.502	11000	F
\smile	To:	Alt	US 58; US	23												

5/3/2016

Virginia Department of Transportation Traffic Engineering Division 2015 Annual Average Daily Traffic Volume Estimates By Section of Route City of Norton

						Oit, O	11401101	•									
Route	Length	AADT	QA	4Tire	Bus	2Axle 3	Tru 3+Axle			QC	K Factor	QK	Dir Factor	AAWDT	QW	Year	
City of Norton																	
C Kantania A	4.00	From	<u> </u>	050/	00/		Th St	40/	00/				0.505	4500	_	0045	
1 Kentucky Ave	1.03	1400	<u>_</u> F_	95%	0%	2%	2%	1%	0%	С	0.085		0.565	1500	F	2015	
							ourn Rd										
	0.00	From	ᄂ	000/	00/		st St	00/	00/				0.54	500	_	0045	
(2)	0.08	510	F	98%	0%	1%	1%	0%	0%	С	0.104		0.54	560	F	2015	
		10					Norton										
O Harriston Do	4 55	From	<u> </u>	000/		t US 58 No			00/				0.504	4600	F	0045	
(3) Hawthorne Dr	1.55	4200 _{To}	F	99%	0%	0%	0%	0%	0%	С	0.091					2015	
					97-75	7 Wise Coe			on								
(1011 O		From	<u> </u>	2.121			Fr US 23								_		
240) 12th St	0.21	7400	F	94%	1%	1%	1%	4%	0%	F	0.086		0.597	8000	F	2015	
		To From			140	6-1 Kentuck	cky Ave @	11th St									
240) 11th St	0.18	6300	F	94%	1%	1%	1%	4%	0%	С	0.100		0.652	6800	F	2015	
240)	00	To	Ė	0.70	. , ,		Park Ave		0 70						•		
		From					Norton				i						
241) Dorchester Rd	1.96	460	F	99%	0%	1%	0%	0%	0%	С	0.097		0.585	500	F	2015	
241)	1.00	То					Norton						0.363		-	_5.0	
		From	1				Park Ave										
242) 12th Street NE	0.28	200	F	99%	0%	1%	0%	0%	0%	F	0.138		0.738	220	F	2015	
242)	••	To	Ė				Norton			-					-		
		From	1			Di	ne St										
10th St		490	F			111	iic st				0.135		0.559	530	F	2015	
10111 01		To		Spruce St									0.000		•	2010	
		From					Avenue				l						
Chesnut Avenue		1000	F			Killic	1 I VOII UC				0.118		0.627	1000	F	2015	
30000		То	Ė			Ridge	Avenue	<u> </u>		3.02.		•	_0.0				
		From	1				ounty Line	Δ			i						
SR 619		180	G	99%	1%	0%	0%	0%	0%	С	0.120		0.5	180	G	2015	
211 717		To				Hoot Ow				-							

5/3/2016 9